

NORTH 1/4 CORNER SECTION 21, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 120 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 21-15-10 ON THE COUNTY LINE. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS WEST ON THE COUNTY LINE TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-15-10
 - 2) 39.95 CHAINS EAST ON THE COUNTY LINE TO THE 15" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-15-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE. **HE SET A STAKE** FOR THE NORTH 1/4 CORNER OF SECTION 21-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.28 CHAINS WEST ON THE COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 21-15-10
 - 2) 40.31 CHAINS EAST ON THE COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE NORTHEAST CORNER OF SECTION 21-15-10

NORTH QUARTER CORNER 21-15-10