

WEST 1/4 CORNER SECTION 21, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 122 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 21-15-10.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-15-10
- 2) 40.00 CHAINS SOUTH TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-15-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 36, A JOINT **PERMANENT SURVEY** IN CONJUNCTION WITH THE WABAUNSEE COUNTY SURVEYOR RECORDED IN SURVEY BOOK "E" ON PAGE 217 DATED JANUARY 2, 1902 ORDERED BY D. C. HOUCK FOR A PERMANENT SURVEY IN SECTIONS 19 & 20 IN TOWNSHIP 15, RANGE 10, SAID THAT **HE FOUND THE GOVERNMENT STONE LYING LOOSE ON THE GROUND** AT THE EAST 1/4 CORNER OF SECTION 20-15-10. AFTER HE RAN THE SECTION LINES FROM THE GOVERNMENT STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-10 TO THE STONE HE THAT FOUND AT THE SOUTHWEST CORNER OF SECTION 29-15-10, HE CORRECTED AND **HE RESET** THE GOVERNMENT STONE FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 20-15-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,326' NORTH TO THE 5" X 12" X 24" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 20-15-10
- 2) 2,652-1/2' NORTH TO THE GOVERNMENT STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE
- 3) 2,652-1/2' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-15-10
- 4) 5,299-1/2' SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 29-15-10
- 5) 7,946-1/2' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-15-10
- 6) 1,300' WEST TO THE 6" X 9" X 20" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 20-15-10
- 7) 2,600' WEST TO THE 5" X 12" X 30" STONE HE SET FOR THE PERMANENT CENTER 1/4 CORNER OF SECTION 20-15-10

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE LYING ON TOP OF THE GROUND SURFACE** AT THE WEST 1/4 CORNER OF SECTION 21-15-10 ON THIS **PERMANENT SURVEY**. **HE RESET THIS STONE AND HE PLACED ANOTHER 24" X 12" X 3" STONE BESIDE THIS RESET STONE**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 20.21 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 21-15-10
- 2) 40.40 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE
- 3) 20.06 CHAINS SOUTH TO THE 18" X 12" X 4" STONE MARKED "H 1/8" HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 21-15-10
- 4) 40.12 CHAINS SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 21-15-10
- 5) 80.12 CHAINS SOUTH TO THE STONE HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 28-15-10
- 6) 120.08 CHAINS SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 28-15-10

WEST QUARTER CORNER 21-15-10