

**WEST 1/16 CORNER NORTHWEST QUARTER SECTION 21, TOWNSHIP 15 SOUTH, RANGE 10 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 36, A JOINT **PERMANENT SURVEY** IN CONJUNCTION WITH THE WABAUNSEE COUNTY SURVEYOR RECORDED IN SURVEY BOOK "E" ON PAGE 217 DATED JANUARY 2, 1902 ORDERED BY D. C. HOUCK FOR A PERMANENT SURVEY IN SECTIONS 19 & 20 IN TOWNSHIP 15, RANGE 10, SAID THAT **HE SET A 5" X 12" X 24" STONE** FOR THE PERMANENT SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 20-15-10 ON LINE AND MIDWAY BETWEEN THE GOVERNMENT STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE AND THE STONE THAT HE FOUND LOOSE ON THE GROUND AND **HE RESET** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 20-15-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,326' NORTH TO THE GOVERNMENT STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE
- 2) 1,326' SOUTH TO THE ORIGINAL STONE HE FOUND LOOSE ON THE GROUND AND **HE RESET** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 20-15-10

**NOTE:** HIS SURVEY DRAWING SHOWS A TOTAL DISTANCE OF 2,652-1/2 BETWEEN THE EAST 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 20-15-10 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR

- 3) 3,978-1/2' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-15-10
- 4) 1,298' WEST TO THE 6" X 9" X 24" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 20-15-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE WEST 1/8<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 21-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.19 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE
- 2) 20.21 CHAINS SOUTH TO THE STONE HE FOUND LYING ON TOP OF THE GROUND AT THE WEST 1/4 CORNER OF SECTION 21-15-10. **HE RESET** THIS STONE AND **HE SET A 24" X 12" X 3" STONE** BESIDE THIS FOUND STONE.
- 3) 40.27 CHAINS SOUTH TO THE 18" X 12" X 4" STONE MARKED "H 1/8" HE SET FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 21-15-10
- 4) 60.33 CHAINS SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 21-15-10
- 5) 100.33 CHAINS SOUTH TO THE STONE IN PLACE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 28-15-10
- 6) 140.29 CHAINS SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 28-15-10

WEST SIXTEENTH CORNER NORTHWEST QUARTER 21-15-10