

NORTH 1/16 CORNER SOUTHEAST QUARTER SECTION 23, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, ALONG WITH W. S. WHITLOCK, WABAUNSEE COUNTY SURVEYOR, IN SURVEY NUMBER 88, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 168 DATED DECEMBER 30, 1903 AT THE REQUEST OF M. W. LANGLEY, W. M. JOHNSON, W. W. PATTERSON, AND J. H. SMITH FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES AND SUBDIVISION OF SECTION 23 AND THE CORNERS AND BOUNDARIES OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 26, ALL IN TOWNSHIP 15 OF RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET AN 18" X 7" X 3" STONE** FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 23-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 14 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 156" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.16 CHAINS EAST TO THE 18" X 7" X 3" STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 23-15-10, FROM WHICH A **WITNESS STONE** STANDS 12 LINKS EAST AND 7 LINKS SOUTH

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 23-15-10