

WEST 1/4 CORNER SECTION 23, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 118 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 13" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 23-15-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 14" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-15-10
 - 2) 40.00 CHAINS SOUTH TO THE 18" X 8" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-15-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 88, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 168 DATED DECEMBER 30, 1903 AT THE REQUEST OF M. W. LANGLEY, W. M. JOHNSON, W. W. PATTERSON, AND J. H. SMITH FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES AND SUBDIVISION OF SECTION 23 AND THE CORNERS AND BOUNDARIES OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 26, ALL IN TOWNSHIP 15 OF RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE 1/4 CORNER STONE** AT THE WEST 1/4 CORNER OF SECTION 23-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 14 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 156" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.01-1/2 CHAINS NORTH TO THE 15" X 9" X 3" STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 23-15-10
 - 2) 40.03 CHAINS NORTH TO THE GOVERNMENT STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 23-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE, IN THE CENTER OF THE ROAD AND IN LINE WITH A FENCE TO THE EAST
 - 3) 40.03 CHAINS SOUTH TO THE 15" X 9" X 5" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 23-15-10, AT 25 FEET NORTH AND 25 FEET EAST OF A STONE CORNER POST
 - 4) 60.07-1/2 CHAINS SOUTH TO THE FLAG HE SET FOR THE WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 26-15-10
 - 5) 80.12 CHAINS SOUTH TO THE FLAG HE SET FOR THE WEST 1/4 CORNER OF SECTION 26-15-10
 - 6) 120.21 CHAINS SOUTH TO THE CALCULATED LOCATION FOR THE SOUTHWEST CORNER OF SECTION 26-15-10 BY THE AFFIDAVIT OF GEORGE McMURDO
 - 7) 200.39 CHAINS SOUTH TO THE CALCULATED LOCATION OF THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL BY LINING WITH TRANSIT BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-15-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-10

WEST QUARTER CORNER 23-15-10