

NORTHWEST CORNER SECTION 24, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 116 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 8" X 6"** FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-15-10 ON THE COUNTY LINE.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH TO THE 22" X 17" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 32 & 24-15-10
 - 2) 80.00 CHAINS SOUTH TO THE 17" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-15-10
 - 3) 40.20 CHAINS EAST ON THE COUNTY LINE TO THE 21" X 7" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 13 & 24-15-10
 - 4) 80.40 CHAINS EAST ON THE COUNTY LINE TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13 & 24-15-10 ON THE EAST TOWNSHIP BOUNDARY

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 60, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 60 DATED SEPTEMBER 2, 1884 FOR A ROAD IN TOWNSHIP 15-10 FOR AUGUST REAKA, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 23-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE TO END THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL TO BEGIN THIS ROAD SURVEY, WITH THE NORTH 2-3/4 MILES BEING 60 FEET WIDE AND THE SOUTH 1/4 MILE BEING 40 FEET WIDE

- 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 413 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 570 TO 572 PETITIONED BY L. A. GRIMSLEY FOR A ROAD IN TOWNSHIPS 15-10 AND 16-10 [PACKET 652 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 22, 1894, WAS ESTABLISHED AS A 40 AND 60 FOOT WIDE ROAD ON OCTOBER 6, 1894 AS NOTED BY J. A. MILLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED BY C. W. WILHITE, COUNTY CLERK, AND RECORDED ON JUNE 28, 1895 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 24-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS 40 FOOT ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE NORTH BANK OF BLUFF CREEK IN THE SOUTHWEST 1/4 OF SECTION 36-15-10, THEN EAST FOR 30 FEET, THEN SOUTH PARALLEL TO THE SECTION LINE AS A 60 FOOT ROAD TO A POINT 30 FEET EAST OF THE SOUTHWEST CORNER OF SECTION 36-15-10 ON THE 3RD STANDARD PARALLEL, THEN CONTINUES WEST ON THE 3RD STANDARD PARALLEL AS A 60 FOOT WIDE ROAD TO THE NORTHWEST CORNER OF SECTION 1-16-10, THEN SOUTH ON THE SECTION LINES AS A 60 FOOT ROAD FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 1-16-10 TO BEGIN THIS ROAD SURVEY

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, ALONG WITH W. S. WHITLOCK, WABAUNSEE COUNTY SURVEYOR, IN SURVEY NUMBER 88, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 168 DATED DECEMBER 30, 1903 AT THE REQUEST OF M. W. LANGLEY, W. M. JOHNSON, W. W. PATTERSON, AND J. H. SMITH FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES AND

SUBDIVISION OF SECTION 23 AND THE CORNERS AND BOUNDARIES OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 26, ALL IN TOWNSHIP 15 OF RANGE 10 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT THE PRORATED DISTANCE BETWEEN THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 14-15-10 IN WABAUNSEE COUNTY AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 23-15-10 FELL **2 LINKS NORTH** OF A **12" X 6" STONE THAT HE FOUND IN THE GROUND AT THE NORTHEAST CORNER OF SECTION 23-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE**. HE NOTED THAT THIS STONE WAS SO NEAR THE POSITION FOR THE TRUE CORNER THAT AN AGREEMENT WAS MADE WITH THE SURVEYOR OF WABAUNSEE COUNTY, WHO WAS PRESENT THAT THE STONE SHOULD BE RECOGNIZED AS THE **TRUE CORNER** ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 14 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 156" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.10 CHAINS NORTH TO THE GOVERNMENT STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 14-15-10 IN WABAUNSEE COUNTY
 - 2) 20.03 CHAINS SOUTH TO THE 15" X 7" X 3" STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 23-15-10
 - 3) 40.06 CHAINS SOUTH TO THE 18" X 7" X 3" STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 23-15-10 FROM WHICH A **WITNESS STONE** STANDS 12 LINKS EAST AND 7 LINKS SOUTH
 - 4) 80.13 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 23-15-10
 - 5) 100.14 CHAINS SOUTH TO THE FLAG HE SET FOR THE EAST 1/2/4 CORNER ON OF THE NE1/4 OF SECTION 26-15-10
 - 6) 120.15 CHAINS SOUTH TO THE FLAG HE SET FOR THE EAST 1/4 CORNER OF SECTION 26-15-10, AT 3 LINKS SOUTH OF THE ROAD STONE HE FOUND MARKED "R" ON THE EAST SIDE
 - 7) 160.18 CHAINS SOUTH TO THE LOCATION FOR THE SOUTHEAST CORNER OF SECTION 26-15-10
 - 8) 2140.23 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL, IN THE CENTER OF THE ROAD AND SOUTH OF A STONE WALL ON THE WEST SIDE OF THE ROAD
 - 9) 40.37 CHAINS WEST ON THE COUNTY LINE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 23-15-10
 - 10) 80.74 CHAINS WEST ON THE COUNTY LINE TO THE GOVERNMENT STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 23-15-10, IN THE CENTER OF THE ROAD AND ON LINE WITH A FENCE TO THE EAST
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 117, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 198 DATED MAY 28, 1905 FOR L. N. NANCE, PRINCIPAL PETITIONER FOR A ROAD ON THE LYON AND WABAUNSEE COUNTY LINE IN TOWNSHIP 15, RANGES 10 & 11, SAID THAT **HE AND WABAUNSEE COUNTY SURVEYOR W. S. WHITLOCK FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 23-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE COUNTY LINE FOR 40.37 CHAINS TO THE STONE THEY FOUND AT THE NORTH 1/4 CORNER OF SECTION 23-15-10, THEN CONTINUES WEST ON THE COUNTY LINE FOR 40.37 CHAINS TO THE STONE THEY FOUND AT THE NORTHWEST CORNER OF SECTION 23-15-10 TO BEGIN THIS ROAD SURVEY

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) THIS ROAD EXTENDS EAST ON THE COUNTY LINE FOR 80.92 CHAINS TO THE 15" X 7" X 3" STONE THEY SET FOR THE NORTHWEST CORNER OF SECTION 19-15-11 ON THE RANGE LINE, THEN CONTINUES EAST ON THE COUNTY LINE FOR 80.28 CHAINS TO THE 20" X 14" X 12" STONE THEY SET FOR THE NORTHWEST CORNER OF SECTION 20-15-11, THEN CONTINUES EAST ON THE COUNTY LINE FOR 50.74 CHAINS TO THE 13" X 8" X 3" STONE THEY SET ON THE INDIAN LINE AT THE NORTHWEST CORNER OF LOT 1 ON THE NORTH SIDE OF THE NE1/4 OF SECTION 20-15-11, AT 29 FEET WEST AND 9 FEET NORTH OF A STONE GATE POST AND 30 FEET WEST OF A STONE WALL, TO END THIS ROAD SURVEY
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 597 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 257 THROUGH 260 PETITIONED BY L. N. NANCE AND OTHERS FOR A ROAD ON THE LYON AND WABAUNSEE COUNTY LINE IN TOWNSHIPS 15-10 AND 15-11 [PACKET 744 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 28, 1905, WAS GRANTED AS A 50 FOOT WIDE ROAD, 25 FEET EACH SIDE OF THE COUNTY LINE, ON APRIL 6, 1905 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND ATTESTED BY W. F. EGGERS, COUNTY CLERK, SAID THAT **HE AND WABAUNSEE COUNTY SURVEYOR W. S. WHITLOCK FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 24-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE COUNTY LINE FOR 40.37 CHAINS TO THE STONE THEY FOUND AT THE NORTH 1/4 CORNER OF SECTION 23-15-10, THEN CONTINUES WEST ON THE COUNTY LINE FOR 40.37 CHAINS TO THE STONE THEY FOUND AT THE NORTHWEST CORNER OF SECTION 23-15-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE COUNTY LINE FOR 80.92 CHAINS TO THE 15" X 7" X 3" STONE THEY SET FOR THE NORTHWEST CORNER OF SECTION 19-15-11 ON THE RANGE LINE, THEN CONTINUES EAST ON THE COUNTY LINE FOR 80.28 CHAINS TO THE 20" X 14" X 12" STONE THEY SET FOR THE NORTHWEST CORNER OF SECTION 20-15-11, THEN CONTINUES EAST ON THE COUNTY LINE FOR 50.74 CHAINS TO THE 13" X 8" X 3" STONE THEY SET ON THE INDIAN LINE AT THE NORTHWEST CORNER OF LOT 1 ON THE NORTH SIDE OF THE NE1/4 OF SECTION 20-15-11, AT 29 FEET WEST AND 9 FEET NORTH OF A STONE GATE POST AND 30 FEET WEST OF A STONE WALL, TO END THIS ROAD SURVEY
 - 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-10 SHOWS A **STONE** AT THE "NE CORNER SECTION 23-15-10" ON THE LYON AND WABAUNSEE COUNTY LINE.
 - 1) 46.9' SW TO THE NORTHWEST CORNER OF A CONCRETE FOUNDATION
 - 2) 45.4' SW TO THE NORTHEAST CORNER OF A CONCRETER FOUNDATION
 - 8) KRETSINGER TIE BOOK NUMBER 13 ON PAGE 36 AT THE BOTTOM OF THE PAGE SHOWS A **LIMESTONE SHOWING ON MARCH 28, 1934** AT THE "NE CORNER SECTION 23-15-10" ON THE LYON AND WABAUNSEE COUNTY LINE. THE FOLLOWING REFERENCES ARE TO THE CORNERS OF AN 18' X 16' CONCRETE FOUNDATION OF A TILE BUILDING:
 - 1) 46.9' SW TO THE NORTH CORNER OF THE FOUNDATION
 - 2) 45.4' SSW TO THE EAST CORNER OF THE FOUNDATION

NORTHWEST CORNER 24-15-10