

NORTH 1/4 CORNER SECTION 26, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 118 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 13" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-15-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.15 CHAINS WEST TO THE 18" X 8" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-15-10
 - 2) 40.15 CHAINS EAST TO THE 17" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-15-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, ALONG WITH W. S. WHITLOCK, WABAUNSEE COUNTY SURVEYOR, IN SURVEY NUMBER 88, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 168 DATED DECEMBER 30, 1903 AT THE REQUEST OF M. W. LANGLEY, W. M. JOHNSON, W. W. PATTERSON, AND J. H. SMITH FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES AND SUBDIVISION OF SECTION 23 AND THE CORNERS AND BOUNDARIES OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 26, ALL IN TOWNSHIP 15 OF RANGE 10 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 13" X 5" X 3" STONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 26-15-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 26-15-10 AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 14 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 156" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.26 CHAINS WEST TO THE 15" X 9" X 5" STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 26-15-10, AT 25 FEET NORTH AND 25 FEET EAST OF A STONE CORNER POST
 - 2) 20.13 CHAINS EAST TO THE 16" X 12" X 4" STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 26-15-10
 - 3) 40.26 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-15-10

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-10 SHOWS A **STONE** AT THE "S1/4 CORNER SECTION 23-15-10".
 - 1) 24.0' NORTH TO A CORNER POST
 - 2) 32.5' NE TO A CEDAR POST
 - 3) 15.0' SOUTH TO A HEDGE CORNER POST

- 4) KRETSINGER TIE BOOK NUMBER 13 ON PAGE 35 AT THE TOP OF THE PAGE SHOWS A **LIMESTONE SHOWING** AT THE "S1/4 CORNER SECTION 23-15-10" ON MARCH 28, 1934.
 - 1) 24.0' NORTH TO HEDGE CORNER FENCE POST
 - 2) 32.5' NE TO 10" CEDAR POST
 - 3) 15.0' SOUTH TO HEDGE CORNER POST FOR FENCES SOUTH & EAST

NORTH QUARTER CORNER 26-15-10