

NORTHWEST CORNER SECTION 27, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 119 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 12" X 10" X 5"** FOR THE CORNER TO SECTIONS 21, 22, 27 & 28-15-10.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH TO THE 16" X 14" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 28-15-10
- 2) 80.00 CHAINS SOUTH TO THE 14" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-15-10
- 3) 39.82 CHAINS EAST TO THE 15" X 13" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 27-15-10
- 4) 79.64 CHAINS EAST TO THE 18" X 8" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-15-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 203 [PACKET 46 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] ON THE PETITION BY JESSE HEAD AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-10, 16-10 AND 17-10 THAT HE SURVEYED ON APRIL 22-24, 1872, AND WAS ORDERED AS A 50 FOOT WIDE ROAD AT A MEETING OF THE COUNTY BOARD HELD MAY 20, 1872 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 27-15-10 ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE CORNER TO SECTIONS 21 & 22-15-10 ON THE LYON AND WABAUNSEE COUNTY TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE WEST 1/4 CORNER OF SECTION 34-15-10 AT A TURN TO THE SOUTHWESTERLY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 137 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 134 TO 136 PETITIONED BY JULIUS HINES AND OTHERS FOR THE VACATION OF ALL THAT PORTION OF WHAT IS KNOWN AS THE "AMERICUS AND ALMA" ROAD RUNNING THROUGH TOWNSHIP 15, RANGE 10 AND RELOCATING THE SAME, [PACKET 385 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 10, 1881, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON OCTOBER 14, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 21-15-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-15-10 ON THE 3RD STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 229 DATED SEPTEMBER 21, 1881, FOR A ROAD SURVEY IN TOWNSHIP 15-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 21-15-10 ON THIS ROAD SURVEY

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-15-10 ON THE 3RD STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER SIX IN SURVEY BOOK "E" ON PAGE 6 DATED FEBRUARY 18-20, 1884, A **PERMANENT SURVEY** TO SUBDIVIDE SECTION 28-15-10 FOR MARSTELLER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 28-15-10 ON THIS **PERMANENT SURVEY**. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 23 ON PAGE 183 IN THE REGISTER OF DEEDS OFFICE ON FEBRUARY 22, 1884, AND SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-10.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 40.01-1/2 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 28-15-10
 - 2) 80.03 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-15-10
 - 3) 20.01-1/2 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 28-15-10
 - 4) 40.03 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 28-15-10
 - 5) 80.06 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-15-10
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 132, A ROAD SURVEY RECORDED IN SURVEY RECORD BOOK "E" ON PAGE 123 FOR ROAD A ROAD IN TOWNSHIPS 15-10 AND 15-11 FOR G. W. GORMAN, PRINCIPAL PETITIONER, DATED DECEMBER 20, 1885, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 22-15-10 TO BEGIN THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE SET AT 902 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 24-15-10, THEN [ANGLE TO RIGHT 8°45'] S. 71°15' E. FOR 722 FEET TO THE STONE HE SET, THEN N. 71°40' E. FOR 215 FEET TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-10 ON THE RANGE LINE; THEN CONTINUES EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 21-15-11 TO THE TERMINUS OF THIS ROAD SURVEY
- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD 319 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 226 TO 228 PETITIONED BY G. W. GORMAN AND OTHERS FOR THE VACATION AND LOCATION OF A COUNTY ROAD IN TOWNSHIPS 15-10 AND 15-11 [PACKET 580 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 2, 1885, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON APRIL 15, 1886 BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 5, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 22-15-10 TO BEGIN THIS ROAD SURVEY. THE ROAD TO BE VACATED WAS PETITIONED AS COMMENCING AT THE EAST CENTER OF SECTION 30-15-11, THENCE RUNNING WEST TWO MILES TO THE CENTER OF THE WEST SIDE OF SECTION 25-15-10 KNOWN AS THE THEODORE HOELLING ROAD. A PENCIL NOTE UNDER THE DRAWING ON PAGE 227 NOTED: THE PORTION OF THE PETITION ASKING FOR THE VACATION OF THE ROAD IN THE CENTER OF SECTIONS 25-15-10 AND 30-15-11 WAS **REJECTED**.

THE ROAD WAS **NOT** VACATED – SEE COMMISSIONERS JOURNAL NUMBER 4 DATED JANUARY 14, 1886.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE SET AT 902 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 24-15-10, THEN [ANGLE TO RIGHT 8°45'] S. 71°15' E. FOR 722 FEET TO THE STONE HE SET, THEN N. 71°40' E. FOR 215 FEET TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-10 ON THE RANGE LINE; THEN CONTINUES EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 21-15-11 TO THE TERMINUS OF THIS ROAD SURVEY

- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 101, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK “F” ON PAGE 97 DATED JUNE 14-16, 1886 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 27-15-10 AND ALSO TO SUBDIVIDE THE EAST 1/2 OF SECTION 27, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 27-15-10 ON THIS **PERMANENT SURVEY**. HE RAN THE SECTION LINES FROM THIS STONE EAST TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 25-15-10 TO RESET THE ORIGINAL GOVERNMENT STONE AT THE NORTHEAST CORNER OF SECTION 27-15-10, AS AFFIRMED BY THE AFFIDAVIT OF WILLIAM A. CURRENS AND W. R. CURRENS. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 36 ON PAGE 498 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 2, 1886, AND SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 15-10.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.46-1/2 CHAINS EAST TO THE 22” X 12” X 5” STONE MARKED “1/4” ON THE NORTH FACE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 27-15-10
- 2) 69.64-1/2 CHAINS EAST TO THE 22” X 6” X 6” STONE MARKED “60” HE SET FOR A PERMANENT PROPERTY CORNER
- 3) 78.93 CHAINS EAST TO THE ORIGINAL GOVERNMENT STONE HE FOUND AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 27-15-10 BY THE AFFIDAVIT OF WILLIAM A. CURRENS AND W. R. CURRENS

- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK “F” ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 12” X 8” X 5” STONE** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 28-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET “M 101” IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION”

- 1) 20.13 CHAINS WEST TO THE 16” X 12” X 4” STONE MARKED “H 1/8” HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 28-15-10
- 2) 40.26 CHAINS WEST TO THE 26” X 6” X 2” STONE MARKED “H 1/4” HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 28-15-10

HIS INFORMATION IS CONTINUED ON PAGE 4

- 3) 80.51 CHAINS WEST TO THE 30" X 12" X 5" STONE THAT HE MARKED THE SAME AS THE ORIGINAL STONE, WHICH IS BURIED BY THE NEW STONE, HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 28-15-10
 - 4) 39.97 CHAINS SOUTH TO THE LOCATION OF THE EAST 1/4 CORNER OF SECTION 28-15-10, AS WITNESSED BY THE STONE MARKED "W 20" HE SET AT 20 FEET WEST AND THE STONE MARKED "E 20" HE SET AT 20 FEET EAST OF THE TRUE POSITION
 - 5) 79.93 CHAINS SOUTH TO THE STONE HE FOUND IN POOR CONDITION AT THE SOUTHEAST CORNER OF SECTION 28-15-10. **HE RESET** THIS STONE AND MARKED "+" ON TOP FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 28-15-10
- 10) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY HOWARD E. BROWN, DEPUTY, IN A ROAD SURVEY FOR ROAD NUMBER 679 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 36 PETITIONED BY J. R. MOORE AND OTHERS FOR THE OPENING AND CONTINUING OF A ROAD IN TOWNSHIP 15-10 [PACKET 901 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE, WAS VIEWED BY THE COUNTY COMMISSIONERS AND HOWARD E. BROWN, DEPUTY COUNTY SURVEYOR, ON AUGUST 12, 1913, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 28-15-10 TO BEGIN THIS ROAD SURVEY. ORDER OF THE BOARD OF COUNTY COMMISSIONERS INCLUDED IN THE REPORT OF VIEW IN PACKET 901:
- THE ABOVE REPORT OF VIEWERS HAVING BEEN READ BEFORE THE BOARD OF COUNTY COMMISSIONERS, AND SAID REPORT BEING FAVORABLE, AND NO LEGAL OBJECTIONS APPEARING AGAINST THE SAME, AND THE BOARD BEING SATISFIED THAT SUCH ROAD WILL BE A PUBLIC UTILITY, DO HEREBY ORDER THAT A PORTION OF SAID ROAD SURVEY AND PLAT BE RECORDED AS RECOMMENDED BY SAID REPORT, WHICH PORTION IS MORE PARTICULARLY DESCRIBED AS FOLLOWS:
- 1) BEGINNING AT A STONE SET IN THE GROUND 5 FEET EAST OF THE WEST LINE OF A NORTH AND SOUTH ROAD ON THE EAST SIDE OF SECTIONS 28 & 21, TOWNSHIP 15 RANGE 10, THENCE WESTERLY ON THE SECTION LINE BETWEEN SECTION 28 AND 21 TOWNSHIP 15, RANGE 10, ONE MILE TO A STONE (MARKED 1 M) THENCE 792 FEET FURTHER ON THE SAME LINE TO A STONE SET IN THE GROUND, TURNED TO AN ANGLE TO RIGHT 39 DEGREES AND AT A DISTANCE OF 1,5125 FEET TO A STONE; THENCE TURNING AN ANGLE TO THE LEFT 42 DEGREES 20 MINUTES, 569 FEET TO A STONE, THENCE ANGLE TO RIGHT 49 DEGREES 35 MINUTES, AND CONTINUING ON THIS LINE TO THE WEST LINE OF THE SOUTHEAST QUARTER OF SECTION 20, TOWNSHIP 15, RANGE 10 EAST, LYON COUNTY, KANSAS AND ENDING THERE
 - 2) IT IS ALSO ORDERED THAT THE TRUSTEE OF THE AFORESAID TOWNSHIP BE DIRECTED TO CAUSE SAID ROAD TO BE OPENED FOR PUBLIC TRAVEL.
 - 3) WITH OF SAID ROAD TO BE FORTY FEET.
 - 4) DONE THIS 8TH DAY OF MAY, 1914. SIGNED BY E. MOORHEAD, CHAIRMAN AND ATTESTED BY H. A. OSBORN, COUNTY CLERK
- 11) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 24
ON JUNE 6, 1913 A PETITION SIGNED BY J. R. MOORE AND OTHERS FOR THE OPENING AND CONTINUING OF A ROAD IN TOWNSHIP 15-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON JULY 2, 1913, AND THE FINAL ORDER FOR THE ROAD ALLOWED WAS ISSUED ON MAY 4, 1913.
- 1) THE ALLOWED ROAD BEGAN AT A STONE SET IN THE GROUND 5 FEET EAST OF THE WEST LINE OF THE NORTH AND SOUTH ROAD ON THE EAST SIDE OF SECTIONS 28 & 21-15-10; THENCE WESTERLY ON THE SECTION LINE BETWEEN SECTIONS 28 & 21-15-10 ONE MILE TO A STONE (MARKED 1 M); THENCE 792

FEET FURTHER ON THE SAME LINE TO A STONE SET IN THE GROUND; TURNED AN ANGLE TO THE RIGHT 39 DEGREES AND AT A DISTANCE OF 1,525 FEET TO A STONE; THENCE TURNING AN ANGLE TO THE LEFT 42 DEGREES 20 MINUTES 569 FEET TO A STONE; THENCE ANGLE TO THE RIGHT 49 DEGREES 35 MINUTES AND CONTINUING ON THIS LINE TO THE WEST LINE OF THE SOUTHEAST QUARTER OF SECTION 20-15-10 AND ENDING THERE

2) ROAD IS 40 FEET WIDE

NORTHWEST CORNER 27-15-10