

**WEST 1/4 CORNER SECTION 27, TOWNSHIP 15 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 119 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 28-15-10.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS NORTH TO THE 12" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 221, 22, 27 & 28-15-10
  - 2) 40.00 CHAINS SOUTH TO THE 14" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-15-10
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER SIX IN SURVEY BOOK "E" ON PAGE 6 DATED FEBRUARY 18-20, 1884, A **PERMANENT SURVEY** TO SUBDIVIDE SECTION 28-15-10 FOR MARSTELLER, SAID THAT **HE SET A STONE** FOR THE EAST 1/4 CORNER OF SECTION 28-15-10 ON LINE AND EQUIDISTANT FROM THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-15-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-15-10 ON THIS **PERMANENT SURVEY**. HIS SURVEY DRAWING INDICATES THAT THIS CORNER IS THE NORTHEAST CORNER OF THE MARSTELLER TRACT. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 23 ON PAGE 183 IN THE REGISTER OF DEEDS OFFICE ON FEBRUARY 22, 1884, AND SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-10.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.01-1/2 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-15-10
  - 2) 40.01-1/2 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-15-10
  - 3) 20.58 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 28-15-10
  - 4) 41.15 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 28-15-10
  - 5) 61.32 CHAINS WEST TO THE STONE SET FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 28-15-10
  - 6) 81.49 CHAINS WEST TO THE STONE HE FOUND ALREADY ESTABLISHED AT THE WEST 1/4 CORNER OF SECTION 28-15-10
  
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 101, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 97 DATED JUNE 14-16, 1886 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 27-15-10 AND ALSO TO SUBDIVIDE THE EAST 1/2 OF SECTION 27-15-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 27-15-10 ON THIS **PERMANENT SURVEY**. HE USED THIS STONE TO SET A STONE MARKED "X" ON THE TOP FOR THE PERMANENT CENTER CORNER OF SECTION 27-15-10. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 36 ON PAGE 498 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 2, 1886, AND SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 15-10.
  
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID

THAT **HE FOUND THE TRUE POINT** FOR THE EAST 1/4 CORNER OF SECTION 28-15-10 ON THIS **PERMANENT SURVEY**. **HE SET A STONE 20 FEET EAST OF THE TRUE POINT MARKED "E 20" AND HE SET A STONE 20 FEET WEST OF THE TRUE POINT MARKED "W 20"**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.97 CHAINS NORTH TO THE 12" X 8" X 5" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 28-15-10
- 2) 60.03 CHAINS NORTH TO THE 18" X 12" X 4" STONE MARKED "H 1/8" HE SET FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 21-15-10
- 3) 80.09 CHAINS NORTH TO THE STONE HE FOUND LYING ON TOP OF THE SURFACE AT THE WEST 1/4 CORNER OF SECTION 21-15-10. **HE RESET THIS STONE AND HE PLACED A 24" X 12" X 3" STONE** BESIDE THE FOUND STONE.
- 4) 100.30 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 21-15-10
- 5) 39.96 CHAINS SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 28-15-10
- 6) 120.49 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE
- 7) 20.12 CHAINS WEST TO THE 15" X 12" X 3" STONE MARKED "1/8" ON THE NORTH AND SOUTH SIDES HE SET FOR THE PERMANENT SOUTH 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 28-15-10
- 8) 40.24 CHAINS WEST TO THE 26" X 12" X 3" STONE MARKED "C 1/4 " HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 28-15-10
- 9) 80.51 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 28-15-10

WEST QUARTER CORNER 27-15-10