

WEST 1/4 CORNER SECTION 28, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 121 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 29-15-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-15-10
 - 2) 40.00 CHAINS SOUTH TO THE 16" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-15-10

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER SIX IN SURVEY BOOK "E" ON PAGE 6 DATED FEBRUARY 18-20, 1884, A **PERMANENT SURVEY** TO SUBDIVIDE SECTION 28-15-10 FOR MARSTELLER, SAID THAT **HE FOUND THE STONE "ALREADY ESTABLISHED"** AT THE WEST 1/4 CORNER OF SECTION 28-15-10 ON THIS **PERMANENT SURVEY**. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 23 ON PAGE 183 IN THE REGISTER OF DEEDS OFFICE ON FEBRUARY 22, 1884, AND SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-10.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.93-1/2 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 28-15-10
 - 2) 39.87 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-15-10
 - 3) 20.17 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE SW1/4 OF SECTION 28-15-10
 - 4) 40.34 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 28-15-10
 - 5) 60.91 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE SE1/4 OF SECTION 28-15-10, AND THE NORTHWEST CORNER OF THE MARSTELLER TRACT
 - 6) 81.49 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 28-15-10, AND THE NORTHEAST CORNER OF THE MARSTELLER TRACT

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 36, A JOINT **PERMANENT SURVEY** IN CONJUNCTION WITH THE WABAUNSEE COUNTY SURVEYOR RECORDED IN SURVEY BOOK "E" ON PAGE 217 DATED JANUARY 2, 1902 ORDERED BY D. C. HOUCK FOR A PERMANENT SURVEY IN SECTIONS 19 & 20 IN TOWNSHIP 15, RANGE 10, SAID THAT **HE FOUND THE GOVERNMENT STONE** AT THE EAST 1/4 CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,647' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-15-10
 - 2) 2,647' NORTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-15-10
 - 3) 5,299-1/2' NORTH TO THE GOVERNMENT STONE HE FOUND LOOSE ON THE GROUND AND HE RESET FOR THE PERMANENT EAST 1/4 CORER OF SECTION 20-15-10
 - 4) 6,625-1/2' NORTH TO THE 5" X 12" X 24" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 20-15-10
 - 5) 7,952' NORTH TO THE GOVERNMENT STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-10

CONTINUED ON PAGE 2

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 96, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 176 DATED AUGUST 16, 1904 ORDERED BY THE SCHOOL BOARD OF DISTRICT 33 TO SURVEY THEIR TRACT 20 RODS NORTH-SOUTH BY 12 RODS EAST-WEST IN THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-15-10, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 84 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 40.00 CHAINS NORTH TO THE 30" X 12" X 3" STONE MARKED THE SAME AS THE ORIGINAL STONE HE FOUND, WHICH IS BURIED BY THE **NEW STONE HE SET**, FOR THE PERMANENT NORTHWEST CORNER OF SECTION 28-15-10
 - 2) 60.06 CHAINS NORTH TO THE 18" X 12" X 4" STONE MARKED "H 1/8" HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 21-15-10
 - 3) 80.12 CHAINS NORTH TO THE STONE HE FOUND LYING ON TOP OF THE SURFACE THAT **HE RESET, PLACING ANOTHER STONE 24" X 12" X 3" STONE BESIDE IT** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 21-15-10
 - 4) 100.33 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 21-15-10
 - 5) 120.52 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE
 - 6) 40.27 CHAINS EAST TO THE 26" X 12" X 3" STONE MARKED "C 1/4" HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 28-15-10
 - 7) 60.39 CHAINS EAST TO THE 15" X 12" X 5" STONE MARKED "1/8" ON THE NORTH & SOUTH SIDES HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE NE1/4 OF SECTION 28-15-10
 - 8) 80.51 CHAINS EAST TO THE **TRUE LOCATION** FOR THE EAST 1/4 CORNER OF SECTION 28-15-10 AS MARKED BY A WITNESS STONE MARKED "E 20" HE SET AT 20 FEET EAST AND A WITNESS STONE MARKED "W 20" HE SET AT 20 FEET WEST OF THE **TRUE LOCATION**

WEST QUARTER CORNER 28-15-10