

NORTH 1/4 CORNER SECTION 29, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 124 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-15-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.76 CHAINS WEST TO THE 16" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-15-10
 - 2) 39.76 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-15-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 36, A JOINT **PERMANENT SURVEY** IN CONJUNCTION WITH THE WABAUNSEE COUNTY SURVEYOR RECORDED IN SURVEY BOOK "E" ON PAGE 217 DATED JANUARY 2, 1902 ORDERED BY D. C. HOUCK FOR A PERMANENT SURVEY IN SECTIONS 19 & 20 IN TOWNSHIP 15, RANGE 10, SAID THAT **HE SET A 5" X 9" X 20" STONE** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 20-15-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 20-15-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-15-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,610' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-15-10
 - 2) 2,610' WEST TO THE 3" X 12" X 18" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 20-15-10
 - 3) 5,236' WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 19-15-10

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 96, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 176 DATED AUGUST 16, 1904 ORDERED BY THE SCHOOL BOARD OF DISTRICT 33 TO SURVEY THEIR TRACT 20 RODS NORTH-SOUTH BY 12 RODS EAST-WEST IN THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-15-10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 84 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL., SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 AND IN PACKET "M 139" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

NORTH QUARTER CORNER 29-15-10