

NORTHWEST CORNER SECTION 29, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 123 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 10" X 4"** FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-15-10.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 30-15-10
- 2) 80.00 CHAINS SOUTH TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-10
- 3) 39.76 CHAINS EAST TO THE 16" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-15-10
- 4) 79.52 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-15-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 36, A JOINT **PERMANENT SURVEY** IN CONJUNCTION WITH THE WABAUNSEE COUNTY SURVEYOR RECORDED IN SURVEY BOOK "E" ON PAGE 217 DATED JANUARY 2, 1902 ORDERED BY D. C. HOUCK FOR A PERMANENT SURVEY IN SECTIONS 19 & 20 IN TOWNSHIP 15, RANGE 10, SAID THAT **HE SET A 3" X 12" X 18" LIMESTONE AT 6 FEET EAST OF A STONE WALL** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 19-15-10 THROUGH THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 19-15-10 TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-15-10, AND THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 17-15-10 IN WABAUNSEE COUNTY SOUTH TO ESTABLISH THIS CORNER.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,626' WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 19-15-10
- 2) 2,641' NORTH TO THE 4" X 12" X 18" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 20-15-10
- 3) 5,290' NORTH TO THE ORIGINAL GOVERNMENT STONE HE FOUND LOOSE ON THE GROUND AND **HE RESET** FOR THE PERMANENT NORTHWEST CORNER OF SECTION 20-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE
- 4) 10,580' NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 17-15-10 IN WABAUNSEE COUNTY
- 5) 2,610' EAST TO THE 5" X 9" X 20" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 20-15-10
- 6) 5,220' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-15-10

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 96, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 176 DATED AUGUST 16, 1904 ORDERED BY THE SCHOOL BOARD OF DISTRICT 33 TO SURVEY THEIR TRACT 20 RODS NORTH-SOUTH BY 12 RODS EAST-WEST IN THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-15-10, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE [AT 6 FEET EAST OF A STONE WALL]** AT THE NORTHWEST CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 84 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE

PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN PLACE [AT 6 FEET EAST OF A STONE WALL]** AT THE NORTHWEST CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.15 CHAINS SOUTH TO THE 40" X 12" X 1-2" STONE MARKED "1/4" ON THE WEST & WEST FACES HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-15-10
- 2) 60.23 CHAINS SOUTH TO THE STAKE HE SET AT 0.14 CHAINS NORTH OF A STONE FENCE POST FOR THE WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 29-15-10
- 3) 80.30 CHAINS SOUTH TO THE GOVERNMENT STONE HE FOUND LYING ON THE GROUND, AND **HE RESET THE ORIGINAL GOVERNMENT STONE MEASURING 14" X 12" X 3" MARKED "+" ON THE TOP** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-15-10, FROM WHICH THE SOUTHWEST CORNER OF STONE FENCE BEARS N. 37° E. AT 0.41 CHAINS
- 4) 160.86 CHAINS SOUTH TO THE STANDING CORNER AT THE SOUTHWEST CORNER OF SECTION 32-15-10 ON THE 3RD STANDARD PARALLEL, FROM WHICH A STONE WALL BEARS WESTERLY AT 1.10 CHAINS

NORTHWEST CORNER 29-15-10