

**WEST 1/4 CORNER SECTION 29, TOWNSHIP 15 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 123 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 30-15-10.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 16" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-15-10
- 2) 40.00 CHAINS SOUTH TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-10

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 4 RECORDED IN SURVEY BOOK "A" ON PAGES 97 & 98 DATED JANUARY 1868 FOR A SURVEY OF 80 ACRES ON THE EAST SIDE OF THE NORTHWEST 1/4, AND THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 30-15-10, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 30-15-10 ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.00 CHAINS WEST TO THE NORTHEAST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 30-15-10
- 2) 40.00 CHAINS WEST TO THE STAKE HE SET FOR THE CENTER OF SEC. 30-15-10
- 3) 60.00 CHAINS WEST TO THE POST HE SET FOR THE SOUTH 1/4/4 CORNER OF THE NW1/4 OF SECTION 30-15-10

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 40" X 12" X 1" TO 12" STONE MARKED "1/4" ON THE EAST AND WEST SIDES** FOR THE WEST 1/4 CORNER OF SECTION 29-15-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-15-10 AND THE ORIGINAL GOVERNMENT STONE THAT HE FOUND AND **HE RESET** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE. HE MARKED THE FOLLOWING

**WITNESS TREES:**

- 1) A 6" BOX ELDER TREE BEARS S. 42-1/2° E. AT 0.20 CHAINS
- 2) AN 8" HACKBERRY TREE BEARS S. 23° W. AT 0.44 CHAINS
- 3) A 12" ELM TREE BEARS N. 40-3/4° W. AT 0.50 CHAINS
- 4) A 14" ELM TREE BEARS N. 54-1/2° E. AT 0.50 CHAINS

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.08 CHAINS SOUTH TO THE STAKE HE SET FOR THE WEST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 29-15-10, AT 0.14 CHAINS NORTH OF THE CENTER OF A STONE FENCE POST
- 2) 40.15 CHAINS SOUTH TO THE ORIGINAL GOVERNMENT STONE HE FOUND LYING ON THE GROUND AND **HE RESET THE ORIGINAL GOVERNMENT STONE MEASURING 14" X 12" X 3" MARKED "+" ON TOP** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-15-10, FROM WHICH THE SOUTHWEST CORNER OF A STONE FENCE BEARS N. 37° 3. AT 0.41 CHAINS

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 120.71 CHAINS SOUTH TO THE STANDING CORNER HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL, FROM WHICH A STONE WALL BEARS WESTERLY AT 1.10 CHAINS
- 4) 40.15 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 29-15-10
- 5) 19.88 CHAINS EAST TO THE 16" X 8" X 3" STONE MARKED "1/8" HE SET FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 29-15-10
- 6) 39.76 CHAINS EAST TO THE 18" X 13" X 4" STONE MARKED "C 1/4" ON ONE SIDE AND "H" ON THE OTHER SIDE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-15-10

WEST QUARTER CORNER 29-15-10