

**WEST 1/16 CORNER SOUTHWEST QUARTER SECTION 29, TOWNSHIP 15 SOUTH, RANGE 10 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 4 RECORDED IN SURVEY BOOK "A" ON PAGES 97 & 98 DATED JANUARY 1868 FOR A SURVEY OF 80 ACRES ON THE EAST SIDE OF THE NORTHWEST 1/4, AND THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4, ALL IN SECTION 30-15-10, SAID THAT **HE DETERMINED THE POSITION** FOR THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 30-15-10 ON THIS SURVEY.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 20.00 CHAINS WEST TO THE SOUTHWEST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 30-15-10
  - 2) 40.00 CHAINS WEST TO THE SOUTHWEST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 30-15-10
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A STAKE** FOR THE WEST 1/8<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-15-10 ON LINE AND HALFWAY BETWEEN THE ORIGINAL GOVERNMENT STONE THAT HE FOUND AND **HE RESET** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-15-10 AND THE STONE THAT HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

**HIS DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 20.08 CHAINS NORTH TO THE 40" X 12" X 1-2" STONE MARKED "1/4" ON THE EAST AND WEST SIDES HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-15-10
- 2) 60.23 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 29-15-10
- 3) 20.07 CHAINS SOUTH TO THE ORIGINAL GOVERNMENT STONE HE FOUND LYING ON THE GROUND AND **HE RESET THE ORIGINAL GOVERNMENT STONE MEASURING 14" X 12" X 3"** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-15-10, FROM WHICH THE SOUTHWEST CORNER OF A STONE FENCE BEARS N. 37° E. AT 0.41 CHAINS
- 4) 100.63 CHAINS SOUTH TO THE STANDING CORNER AT THE SOUTHWEST CORNER OF SECTION 32-15-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL, FROM WHICH A STONE WALL BEARS WESTERLY AT 1.10 CHAINS

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 29-15-10