

**NORTH 1/4 CORNER SECTION 31, TOWNSHIP 15 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 123 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-15-10.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 39.60 CHAINS WEST TO THE 14" X 2" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-15-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE
  - 2) 40.00 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-10
  
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 3 RECORDED IN SURVEY BOOK "A" ON PAGE 96 DATED JANUARY 1868 TO SURVEY PART OF R. McMILLAN'S LAND, BEING THE ASCERTAINING THAT THE 1/4 CORNER ON THE NORTH SIDE OF SECTION 31-15-10 WAS WHERE THE GOVERNMENT SURVEYORS PLACE IT, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 31-15-10 ON THIS SURVEY. AFTER SURVEYING NORTH TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-15-10, HE NOTED THAT IT WAS 10 LINKS TO FAR NORTH AND "DECIDED IT WAS WHERE THE GOVERNMENT PLACED IT".  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 80.10 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 31-15-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL
  - 2) 80.00 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-15-10
  
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 4 RECORDED IN SURVEY BOOK "A" ON PAGES 97 & 98 DATED JANUARY 1868 FOR A SURVEY OF 80 ACRES ON THE EAST SIDE OF THE NORTHWEST 1/4, AND THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 30-15-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 30-15-10 ON THIS SURVEY.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 20.00 CHAINS NORTH TO THE POST HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 30-15-10
  - 2) 40.00 CHAINS NORTH TO THE STAKE HE SET FOR THE CENTER CORNER OF SECTION 30-15-10
  - 3) 60.00 CHAINS NORTH TO THE POST HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE NE1/4 OF SECTION 30-15-10
  - 4) 80.00 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-15-10
  
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 30-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.80 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE
- 2) 39.94 CHAINS EAST TO THE ORIGINAL GOVERNMENT STONE HE FOUND LYING ON THE GROUND AT THE NORTHEAST CORNER OF SECTION 31-15-10. **HE RESET THE ORIGINAL GOVERNMENT STONE MEASURING 14" X 12" X 3" MARKED "+" ON TOP** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 31-15-10, FROM WHICH THE SOUTHWEST CORNER OF A STONE FENCE BEARS N. 37° E. AT 0.41 CHAINS
- 3) 59.90 CHAINS EAST TO THE 18" X 6" X 5" STONE MARKED "H 1/8" HE SET FOR THE PERMANENT SOUTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 29-15-10, FROM WHICH THE SOUTHEAST CORNER OF A GATE POST BEARS N. 27° W. AT 0.44 CHAINS
- 4) 79.86 CHAINS EAST TO THE STONE HE FOUND IN POOR CONDITION AT THE SOUTH 1/4 CORNER OF SECTION 29-15-10. **HE SET A 15" X 8" X 8" STONE MARKED "1/4" ON THE NORTH AND SOUTH SIDES** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-15-10

NORTH QUARTER CORNER 31-15-10