

**NORTHWEST CORNER SECTION 31, TOWNSHIP 15 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 29 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 12" X 3"** FOR THE CORNER TO SECTIONS 30 & 31-15-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.60 CHAINS EAST TO THE 20" X 16" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-15-10
  - 2) 79.60 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-10
  - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 31-15-10
  - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 28" X 9" X 5" LIMESTONE THEY SET ON A LEVEL PLAIN NEAR TIMBER AST THE CORNER TO TOWNSHIP 15, SOUTH, RANGES 9 & 10 EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 3 RECORDED IN SURVEY BOOK "A" ON PAGE 96 DATED JANUARY 1868 TO SURVEY PART OF R. McMILLAN'S LAND, BEING THE ASCERTAINING THAT THE 1/4 CORNER ON THE NORTH SIDE OF SECTION 31-15-10 WAS WHERE THE GOVERNMENT SURVEYORS PLACE IT, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS SURVEY.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 40.00 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 31-15-10
  - 2) 80.00 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-10
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 53 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 214 TO 216 PETITION BY E. W. McMILLAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 15-10 [PACKET 114 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 10, 1879, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JANUARY 7, 1880, AND WAS RECORDED ON JANUARY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE *NORTHEAST* CORNER OF SECTION 31-15-10 FOR THE TERMINUS OF THIS ROAD SURVEY. [**NOTE:** HIS SURVEY NOTES AND DRAWING INDICATE THAT HE ENDED THIS ROAD SURVEY AT THE *NORTHWEST* CORNER OF SECTION 31-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,103'; THEN DEVIATES BOTH NORTH AND SOUTH OF THE SECTION LINES TO INTERSECT THE SECTION LINE AT THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 31-15-10; THEN CONTINUES EAST ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 34-15-10 TO COMMENCE THIS ROAD SURVEY
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 177 DATED OCTOBER 10, 1879, FOR A COUNTY ROAD IN TOWNSHIP 15-10, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO END THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,103 FEET TO AN ANGLE STONE HE SET ON THIS ROAD SURVEY

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 22, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 203 DATED MAY 2-3, 1901 GAVE NOTICE THAT A SURVEY WILL BE MADE IN SECTION 25, TOWNSHIP 15, RANGE 19 BY F. H. HANNAH, MORRIS COUNTY SURVEYOR, AND THAT HE WOULD ATTEND AND WITNESS THE SURVEY IN THE INTEREST OF THE RESIDENTS OF LYON COUNTY, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 30-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY** ON THE COUNTY LINE. HIS SURVEY NOTES SAID THAT HE SET THE PERMANENT NORTHWEST CORNER OF SECTION 30-15-10 IN LINE WITH THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 30-15-10 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-15-10, LEAVING THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-15-10 AT 1-1/3 FEET EAST OF THIS LINE. THERE IS ADDITIONAL INFORMATION IN PACKET "M 52" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.07-1/2 CHAINS NORTH ON THE RANGE LINE AND COUNTY LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-15-10 LOCATED 1-1/3 FEET EAST OF THE LINE FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-15-10 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 30-15-10
- 2) 60.12 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 30-15-10
- 3) 80.15 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE 3" X 8" X 18" STONE MARKED "X" ON THE WEST FACE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 30-15-10

- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTHWEST CORNER OF SECTION 30-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.80 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/4 CORNER OF SECTION 30-15-10
- 2) 79.94 CHAINS EAST TO THE ORIGINAL GOVERNMENT STONE HE FOUND LYING ON THE GROUND AT THE SOUTHWEST CORNER OF SECTION 29-15-10. **HE RESET THE ORIGINAL GOVERNMENT STONE MEASURING 14" X 12" X 3" MARKED "+" ON TOP** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION

29-15-10, FROM WHICH THE SOUTHWEST CORNER OF A STONE FENCE BEARS N. 37° E. AT 0.41 CHAINS

- 3) 99.70 CHAINS EAST TO THE 18" X 6" X 6" STONE MARKED "H 1/8" HE SET FOR THE PERMANENT SOUTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 29-15-10, FROM WHICH THE SOUTHEAST CORNER OF A GATE POST BEARS N. 27° W. AND 0.44 CHAINS
  - 4) 119.66 CHAINS EAST TO THE STONE HE FOUND IN POOR CONDITION AT THE SOUTH 1/4 CORNER OF SECTION 29-15-10, AND **HE RESET WITH A 15" X 8" X 8" STONE MARKED "1/4" ON THE NORTH AND SOUTH SIDES AND "+" ON TOP** HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29
- 7) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY HOWARD E. BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 689 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 46 PETITIONED BY J. W. GRAY AND OTHERS FOR A ROAD ON THE LYON AND MORRIS COUNTY LINE IN TOWNSHIP 15-10 [PACKET 933 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE DEPUTY COUNTY SURVEYOR ON AUGUST 14, 1914 AND WAS APPROVED AS A 40 FOOT WIDE ROAD ON DECEMBER 9, 1914 BY A JOINT MEETING WITH THE BOARD OF MORRIS COUNTY AS NOTED BY E. MOORHEAD, CHAIRMAN OF THE BOARD OF LYON COUNTY COMMISSIONERS, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO BEGIN THIS ROAD SURVEY. HE SAID THAT THIS ROAD SURVEY ON THE COUNTY LINE WAS MADE IN CONJUNCTION WITH MORRIS COUNTY SURVEYOR ARTHUR SMITH.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 31-15-10 WE RAN SOUTH ON THE SECTION LINE BETWEEN SECTION 31-15-10 AND SECTION 36-15-9 VA 8°20' FOR 2,831 FEET TO A STONE; THENCE S. 45° W. FOR 241 FEET; THENCE S. 7°26' W. FOR 356.4 FEET; THENCE S. 35°22' W. FOR 264 FEET; THENCE S. 25°22' W. FOR 412.25 FEET; THENCE S. 2°08' E. FOR 276.5 FEET CROSSING A CREEK; THENCE S. 73°28' E. FOR 232 FEET; THENCE S. 32°13' E. FOR 85.8 FEET; THENCE S. 2°08' E. FOR 330 FEET; THENCE S. 18°64' E. FOR 198 FEET; THENCE S. 47°74' E. FOR 264 FEET; THENCE S. 23°54' E. FOR 132.5 FEET TO A STONE IN THE PUBLIC ROAD SET IN A FORMER ROAD SURVEY AND THERE ENDING
  - 2) ALL ANGLES ARE MARKED BY LIMESTONES SET IN THE GROUND
- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-10 SHOWS A **STONE** AT THE "SW CORNER SECTION 30-15-10" ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE.
- 1) 34' NW TO A CORNER POST
  - 2) 33.5' NE TO A CORNER POST
  - 3) 36.5' SE TO A CORNER POST
  - 4) 37.5' SE TO A CORNER POST
- 9) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 64 AT THE BOTTOM OF THE PAGE SHOWS A **CORNERSTONE** AT THE "SW CORNER SECTION 30-15-10" ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE.
- 1) 40.0' NW TO A 3/4" ROUND IRON PIN
  - 2) 37.0' SW TO THE NEAR FACE OF A CORNER FENCE POST
  - 3) 33.6' NE TO THE NEAR FACE OF A CORNER FENCE POST
  - 4) 36.6' SE TO THE NEAR FACE OF A CORNER FENCE POST

NORTHWEST CORNER 31-15-10