

NORTH 1/4 CORNER SECTION 32, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 123 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-15-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.90 CHAINS WEST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-10
 - 2) 79.80 CHAINS EAST TO THE 16" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-15-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 566 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 129 THROUGH 132 PETITION BY W. J. HAMAKER AND OTHERS FOR HE RELOCATION AND VACATION OF A ROAD IN TOWNSHIP 15-10 [PACKET 709 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON APRIL 23, 1901, WAS ESTABLISHED AND OPENED AS A 40 FOOT WIDE ROAD, 20 FEET ON EACH SIDE OF THE SURVEYED LINE, ON AUGUST 9, 1901 AS NOTED BY JOHN LANGLEY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON AUGUST 28 1901 BY ALVA J. SMITH, COUNTY SURVEYOR, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 32-15-10. HE BEGAN THIS ROAD RELOCATION SURVEY AT A 4" X 9" X 14" STONE IN THE CENTER OF THE ROAD ON THE SECTION LINE ABOUT 600 FEET WEST OF THIS CORNER.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) FROM THE 4" X 9" X 14" STONE HE SET TO BEGIN THIS ROAD RELOCATION SURVEY HE RAN S. 60°45' E. FOR 326 FEET TO THE ROAD STONE HE SET, THENCE N. 59°30' E. FOR 525 FEET TO THE ROAD STONE HE SET ON THE SECTION LINE TO END THIS ROAD RELOCATION AT 2,404 FEET WEST OF THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-15-10
 - 2) THAT PORTION OF ROAD NUMBER 6 IN TOWNSHIP 15-10 LAYING ON THE SECTION LINE BETWEEN THE POINTS WHERE THIS ROAD LEAVES THE SECTION LINE AND AGAIN INTERSECTS THE SECTION LINE WAS **VACATED**

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 27, A ROAD RELOCATION SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 208 FOR A ROAD IN TOWNSHIP 15-10 FOR W. J. HAMAKER, PRINCIPAL PETITIONER, DATED APRIL 23, 1901, SAID THAT HE BEGAN THIS ROAD SURVEY AT A STONE 4" X 9" X 14" IN THE CENTER OF THE ROAD ON THE SECTION LINE ABOUT 600 FEET WEST OF THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 32-15-10, THEN S. 60°45' E. FOR 326 FEET TO A STONE, THEN N. 59°30' E. TO THE SECTION LINE TO A POINT 2,404' WEST OF THE NORTHEAST CORNER OF SECTION 32-15-10 TO THE TERMINUS OF THIS ROAD RELOCATION SURVEY.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 96, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 176 DATED AUGUST 16, 1904 ORDERED BY THE SCHOOL BOARD OF DISTRICT 33 TO SURVEY THEIR TRACT 20 RODS NORTH-SOUTH BY 12 RODS EAST-WEST IN THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-15-10, SAID THAT **HE SET A STONE** FOR THE SOUTH 1/4 CORNER OF SECTION 29-15-10 ON TRANSIT LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-15-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 84 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 12 RODS WEST TO THE 15" X 12" X 5" PERMANENT PROPERTY STONE HE SET FOR THE SOUTHWEST CORNER OF THE SCHOOL DISTRICT TRACT
 - 2) 7.83 CHAINS WEST TO THE STONE HE ON THE SECTION LINE AT AN ANGLE IN THE ROAD
 - 3) 39.82 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-15-10, ON LINE WITH THE FENCES NORTH AND SOUTH
 - 4) 39.82 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-15-10
 - 5) 20 RODS NORTH TO THE 22" X 12" X 4" PERMANENT PROPERTY STONE HE SET FOR THE NORTHEAST CORNER OF THE SCHOOL DISTRICT TRACT
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN POOR CONDITION** AT THE SOUTH 1/4 CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. **HE REPLACED THIS FOUND STONE WITH A 15" X 8" X 8" STONE MARKED "1/4" ON THE NORTH AND SOUTH SIDES AND "+" ON THE TOP** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-15-10. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.96 CHAINS WEST TO THE 18" X 6" X 5" STONE MARKED "H 1/8" HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 29-15-10, FROM WHICH THE SOUTHEAST CORNER OF A GATE POST BEARS N. 27° W. AT 0.44 CHAINS
- 2) 39.92 CHAINS WEST TO THE ORIGINAL GOVERNMENT STONE HE FOUND LYING ON THE GROUND AT THE SOUTHWEST CORNER OF SECTION 29-15-10. **HE RESET** THE ORIGINAL GOVERNMENT STONE MEASURING 14" X 12" X 3" MARKED "+" ON TOP FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-15-10, FROM WHICH THE SOUTHWEST CORNER OF A STONE FENCE BEARS N. 37° E. AT 0.41 CHAINS
- 3) 79.86 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/4 CORNER OF SECTION 30-15-10
- 4) 119.66 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 30-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE
- 5) 20.07 CHAINS NORTH TO THE 30" X 8" X 3" STONE MARKED "H 1/8" HE SET FOR THE PERMANENT EAST 1/8TH CORNER OF THE SW1/4 OF SECTION 29-15-10
- 6) 40.13 CHAINS NORTH TO THE 18" X 13" X 4" STONE MARKED "C 1/4" ON ONE SIDE AND "H" ON THE OTHER SIDE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-15-10

NORTH QUARTER CORNER 32-15-10