

NORTHWEST CORNER SECTION 32, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 122 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING DISTANCES:
 - 1) 40.00 CHAINS SOUTH TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 31 & 32-15-10
 - 2) 80.00 CHAINS SOUTH TO THE 20" X 11" X 4" LIMESTONE THEY SET NEAR THE TOP OF A STONEY HILL FOR THE CORNER TO SECTIONS 31 & 32-15-10 ON THE 4TH STANDARD PARALLEL
 - 3) 39.90 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-15-10
 - 4) 79.80 CHAINS EAST TO THE 16" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-15-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 53 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 214 TO 216 PETITION BY E. W. McMILLAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 15-10 [PACKET 114 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 10, 1879, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JANUARY 7, 1880, AND WAS RECORDED ON JANUARY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 32-15-10 ON THIS ROAD SURVEY'
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 31-15-10; THEN DEVIATES TO THE SOUTHWEST BEFORE IT INTERSECTS THE SECTION LINE AND DEVIATES TO THE NORTH SIDE OF THE SECTION LINE; AND INTERSECTS THE SECTION LINE AT 2,103' EAST OF THE NORTHWEST CORNER OF SECTION 31-15-1-, THEN CONTINUES WEST ON THE SECTION LINE TO THE NORTHWEST CORNER OF SECTION 31-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 34-15-10 TO COMMENCE THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 177 DATED OCTOBER 10, 1879, FOR A COUNTY ROAD IN TOWNSHIP 15-10, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 32-15-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE ROAD EXTENDS WEST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 31-15-10 AT AN ANGLE STONE IN THE ROAD SURVEY
 - 2) THE ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-15-10 TO COMMENCE THIS ROAD SURVEY

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 96, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 176 DATED AUGUST 16, 1904 ORDERED BY THE SCHOOL BOARD OF DISTRICT 33 TO SURVEY THEIR TRACT 20 RODS NORTH-SOUTH BY 12 RODS EAST-WEST IN THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-15-10, SAID THAT **HE FOUND THE STONE ON LINE WITH THE FENCES NORTH AND SOUTH** AT THE SOUTHWEST CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS

FIELD NOTES ARE IN BOOK 2 ON PAGE 84 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION

- 1) 31.99 CHAINS EAST TO THE STONE HE FOUND ON THE SECTION LINE AT AN ANGLE IN THE ROAD
- 2) 39.82 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-15-10
- 3) 70.64 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-15-10

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT HE FOUND THE ORIGINAL GOVERNMENT STONE AT THE SOUTHWEST CORNER OF SECTION 29-15-10 LYING ON THE GROUND. AFTER CHECKING AGAINST OTHER STONES, **HE RESET THIS ORIGINAL GOVERNMENT STONE MEASURING 14" X 12" X 3" AND MARKED WITH A PLUS ("+") ON THE TOP** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-15-10. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 1) THE SOUTHWEST CORNER OF A STONE FENCE POST BEARS N. 37° E. AT A DISTANCE OF 0.41 CHAINS
- 2) A STONE WALL BEARS WESTERLY AT 1.10 CHAINS

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.94 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/4 CORNER OF SECTION 30-15-10
 - 2) 79.74 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 30-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE
 - 3) 80.56 CHAINS SOUTH TO THE STANDING CORNER HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-10 ON THE 3RD STANDARD PARALLEL, FROM WHICH A STONE WALL BEARS WESTERLY AT 1.10 CHAINS
 - 4) 20.07 CHAINS NORTH TO THE STAKE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 29-15-10, AT 0.14 CHAINS NORTH FROM THE CENTER OF A STONE FENCE POST
 - 5) 40.15 CHAINS NORTH TO THE 40" X 12" X 1-2" STONE MARKED "1/4" ON THE EAST AND WEST SIDES HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-15-0
 - 6) 80.30 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 29-15-10
 - 7) 19.96 CHAINS EAST TO THE 18" X 6" X 5" STONE MARKED "H 1/8" HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 29-15-10, FROM WHICH THE SOUTHEAST CORNER OF A GATE POST BEARS N. 27° W. AT 0.44 CHAINS
 - 8) 39.92 CHAINS EAST TO THE STONE HE FOUND IN POOR CONDITION AT THE SOUTH 1/4 CORNER OF SECTION 29-15-10. **HE SET A 15" X 8" X 8" STONE MARKED "1/4" ON THE NORTH AND SOUTH SIDES AND A "+" ON THE TOP** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-15-10
- NORTHWEST CORNER 32-15-10