

SOUTHWEST CORNER SECTION 32, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 2 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 11" X 4"** NEAR THE TOP OF A STONEY HILL FOR THE CORNER TO SECTIONS 31 & 32-15-10 ON THE 3RD STANDARD PARALLEL ON OCTOBER 1, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 24" X 8" X 3" LIMESTONE THEY SET ON THE NORTHEAST SLOPE OF A STONY POINT FOR THE SOUTH 1/4 CORNER OF SECTION 32-15-10
- 2) 80.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 18" X 6" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 32 & 33-15-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 5, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 185 DATED APRIL 2-4 AND MAY 8-9, 1900 AT THE ORDER OF THE RICHARDS BROTHERS FOR A SURVEY OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 6-16-10, SAID THAT **HE FOUND THE STANDARD CORNER STONE** AT THE SOUTHEAST CORNER OF SECTION 31-15-10 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 50" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 3.25 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE CLOSING CORNER STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 6-16-10
- 2) 80.00 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE STANDARD CORNER STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 6-16-10

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE STANDING** AT THE SOUTHWEST CORNER OF SECTION 32-15-10 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 1) A STONE WALL REARS WESTERLY AT 1.10 CHAINS

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 80.56 CHAINS SOUTH TO THE ORIGINAL GOVERNMENT STONE HE FOUND LYING ON THE GROUND AT THE SOUTHWEST CORNER OF SECTION 29-15-10. **HE RESET THE ORIGINAL GOVERNMENT STONE MEASURING 14" X 12" X 3" MARKED "+" ON TOP** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-15-10, FROM WHICH THE SOUTHWEST CORNER OF A STONE FENCE BEARS N. 37° E. AT 0.41 CHAINS
- 2) 100.63 CHAINS NORTH TO THE STAKE HE SET FOR THE WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 32-15-10
- 3) 120.71 CHAINS NORTH TO THE 40" X 12" X 1-2" STONE MARKED "1/4" ON THE EAST AND WEST SIDES HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-15-10

HIS INFORMATION IS CONTINUED ON PAGE 2

4) 160.86 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE
NORTHWEST CORNER OF SECTION 29-15-10

SOUTHWEST CORNER 32-15-10