

WEST 1/4 CORNER SECTION 32, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 122 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 31 & 32-15-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-15-10
 - 2) 40.00 CHAINS SOUTH TO THE 20" X 11" X 4" LIMESTONE THEY SET NEAR THE TOP OF A STONEY HILL FOR THE CORNER TO SECTIONS 31 & 32-15-10 ON THE 4TH STANDARD PARALLEL

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 32-15-10 ON THIS **PERMANENT SURVEY** AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-15-10 ON THE 3RD STANDARD PARALLEL NORTH TO THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 29-15-10. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

WEST QUARTER CORNER 32-15-10