

NORTHWEST CORNER SECTION 33, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 120 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 16" X 3"** FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-15-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 32 & 33-15-10
 - 2) 80.00 CHAINS SOUTH TO THE 18" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 32 & 33-15-10 ON THE 3RD STANDARD PARALLEL
 - 3) 40.00 CHAINS EAST TO THE 24" X 10" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-15-10
 - 4) 80.00 CHAINS EAST TO THE 14" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-15-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 53 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 214 TO 216 PETITION BY E. W. McMILLAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 15-10 [PACKET 114 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 10, 1879, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JANUARY 7, 1880, AND WAS RECORDED ON JANUARY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 33-15-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 31-15-10; THEN DEVIATES TO THE SOUTHWEST BEFORE IT INTERSECTS THE SECTION LINE AND DEVIATES TO THE NORTH SIDE OF THE SECTION LINE; AND INTERSECTS THE SECTION LINE AT 2,103' EAST OF THE NORTHWEST CORNER OF SECTION 31-15-1-, THEN CONTINUES WEST ON THE SECTION LINE TO THE NORTHWEST CORNER OF SECTION 31-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 34-15-10 TO COMMENCE THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 177 DATED OCTOBER 10, 1879, FOR A COUNTY ROAD IN TOWNSHIP 15-10, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 33-15-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 31-15-10 AT AN ANGLE STONE IN THE ROAD SURVEY
 - 2) THE ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-15-10 TO COMMENCE THIS ROAD SURVEY

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER SIX IN SURVEY BOOK "E" ON PAGE 6 DATED FEBRUARY 18-20, 1884, A **PERMANENT SURVEY** TO SUBDIVIDE SECTION 28-15-10 FOR MARSTELLER, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 28-15-10 ON THIS **PERMANENT SURVEY**. THIS SURVEY IS RECORDED IN MISCELLANEOUS VOLUME 23 ON PAGE 183 IN THE REGISTER OF DEEDS OFFICE, AND SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-10.

CONTINUED ON PAGE 2

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 566 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 129 THROUGH 132 PETITION BY W. J. HAMAKER AND OTHERS FOR HE RELOCATION AND VACATION OF A ROAD IN TOWNSHIP 15-10 [PACKET 709 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON APRIL 23, 1901, WAS ESTABLISHED AND OPENED AS A 40 FOOT WIDE ROAD, 20 FEET ON EACH SIDE OF THE SURVEYED LINE, ON AUGUST 9, 1901 AS NOTED BY JOHN LANGLEY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON AUGUST 28 1901 BY ALVA J. SMITH, COUNTY SURVEYOR, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 32-15-10 ON THIS ROAD RELOCATION. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) HE RAN WEST ON THE SECTION LINE FOR 2,404 FEET TO THE ROAD STONE HE SET TO END THIS ROAD RELOCATION SURVEY, THEN S. 59°30' W. FOR 525 FEET TO THE ROAD STONE HE SET, THEN N. 60°45' W. FOR 326 FEET TO THE 4" X 9" X 14" STONE HE SET IN THE CENTER OF THE ROAD ON THE SECTION LINE ABOUT 600 FEET WEST OF THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 32-15-10 TO BEGIN THIS ROAD RELOCATION SURVEY
 - 2) THAT PORTION OF ROAD NUMBER 6 IN TOWNSHIP 15-10 LAYING ON THE SECTION LINE BETWEEN THE POINTS WHERE THIS ROAD LEAVES THE SECTION LINE AND AGAIN INTERSECTS THE SECTION LINE WAS **VACATED**
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 27, A ROAD RELOCATION SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 208 FOR A ROAD IN TOWNSHIP 15-10 FOR W. J. HAMAKER, PRINCIPAL PETITIONER, DATED APRIL 23, 1901, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 32-15-10 ON THIS ROAD RELOCATION SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) HE RAN WEST ON THE SECTION LINE FOR 2,404 FEET TO THE ROAD STONE HE SET TO END THIS ROAD RELOCATION SURVEY, THEN S. 59°30' W. FOR 525 FEET TO THE ROAD STONE HE SET, THEN N. 60°45' W. FOR 326 FEET TO THE 4" X 9" X 14" STONE HE SET IN THE CENTER OF THE ROAD ON THE SECTION LINE ABOUT 600 FEET WEST OF THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 32-15-10 TO BEGIN THIS ROAD RELOCATION SURVEY
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 36, A JOINT **PERMANENT SURVEY** IN CONJUNCTION WITH THE WABAUNSEE COUNTY SURVEYOR RECORDED IN SURVEY BOOK "E" ON PAGE 217 DATED JANUARY 2, 1902 ORDERED BY D. C. HOUCK FOR A PERMANENT SURVEY IN SECTIONS 19 & 20 IN TOWNSHIP 15, RANGE 10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**, HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,647' NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 29-15-10
 - 2) 5,294' NORTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-15-10
 - 3) 7,946.5' NORTH TO THE ORIGINAL GOVERNMENT STONE HE FOUND LOOSE ON THE GROUND AND **HE RESET** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 20-15-10
 - 4) 9,272-1/2' NORTH TO THE 5" X 12" X 24" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 20-15-10
 - 5) 10,599' NORTH TO THE GOVERNMENT STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE

CONTINUED ON PAGE 3

- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 96, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 176 DATED AUGUST 16, 1904 ORDERED BY THE SCHOOL BOARD OF DISTRICT 33 TO SURVEY THEIR TRACT 20 RODS NORTH-SOUTH BY 12 RODS EAST-WEST IN THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-15-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 29-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 84 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 39.82 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-15-10
 - 2) 39.82 CHAINS AND 20 RODS WEST TO THE 15" X 12" X 5" STONE HE SET FOR THE PERMANENT PROPERTY CORNER AT THE SOUTHWEST CORNER OF THE SCHOOL DISTRICT TRACT
 - 3) 47.65 CHAINS WEST TO THE STONE HE FOUND ON THE SECTION LINE AT AN ANGLE IN THE ROAD
 - 4) 79.64 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-15-10 ON LINE WITH THE FENCES NORTH AND SOUTH
- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 28-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 101" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 20.12 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 28-15-10
 - 2) 40.24 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT 6" UNDER THE SOIL AND **HE RESET** IN THE SAME PLACE AT THE SOUTH 1/4 CORNER OF SECTION 28-16-10
 - 3) 80.42 CHAINS EAST TO THE STONE HE FOUND IN POOR CONDITION AT THE SOUTHEAST CORNER OF SECTION 32-16-10. **HE RESET** THE STONE AND MARKED A "+" ON THE TOP OF THE STONE
 - 4) 39.96 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 28-16-10
 - 5) 79.96 CHAINS NORTH TO THE ORIGINAL GOVERNMENT STONE AT THE NORTHWEST CORNER OF SECTION 29-16-10. HE SET A 30" X 13" X 3" STONE MARKED THE SAME AS THE ORIGINAL STONE, WHICH IS BURIED BY THE NEW STONE, FOR THE PERMANENT NORTHWEST CORNER OF SECTION 29-16-10

NORTHWEST CORNER 33-15-10