

**NORTH 1/4 CORNER SECTION 34, TOWNSHIP 15 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 117 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-15-10.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 39.80 CHAINS WEST TO THE 14" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-15-10
  - 2) 39.80 CHAINS EAST TO THE 20" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-15-10
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 101, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 97 DATED JUNE 14-16, 1886 TO ESTABLISH THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 27-15-10 AND ALSO TO SUBDIVIDE THE EAST 1/2 OF SECTION 27-15-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 27-15-10 ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONE THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 27-15-10 TO SET THE PERMANENT CENTER CORNER OF SECTION 27-15-10. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 36 ON PAGE 498 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 2, 1886, AND SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 15-10.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 19.87 CHAINS NORTH TO THE 16" X 6" X 2" STONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 27-15-10
  - 2) 39.74 CHAINS NORTH TO THE STONE MARKED "X" ON TOP HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 27-15-10
  - 3) 59.48 CHAINS NORTH TO THE PROPERTY STONE MARKED "60" HE SET
  - 4) 79.48 CHAINS NORTH TO THE 22" X 12" X 5" STONE MARKED "1/4" ON THE NORTH FACE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 27-15-10

NORTH QUARTER CORNER 34-15-10