

NORTHWEST CORNER SECTION 34, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 119 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 12" X 5"** FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-15-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH TO THE 16" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-15-10
 - 2) 80.00 CHAINS SOUTH TO THE 18" X 11" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 33 & 34-15-10 ON THE 3RD STANDARD PARALLEL
 - 3) 39.80 CHAINS EAST TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-15-10
 - 4) 79.60 CHAINS EAST TO THE 20" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-15-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 203 [PACKET 46 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] ON THE PETITION BY JESSE HEAD AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-10, 16-10 AND 17-10 THAT HE SURVEYED ON APRIL 22-24, 1872, AND WAS ORDERED AS A 50 FOOT WIDE ROAD AT A MEETING OF THE COUNTY BOARD HELD MAY 20, 1872 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-15-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE WEST 1/4 CORNER OF SECTION 34-15-10 AT A TURN TO THE SOUTHWESTERLY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 53 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 214 TO 216 PETITION BY E. W. McMILLAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 15-10 [PACKET 114 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 10, 1879, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JANUARY 7, 1880, AND WAS RECORDED ON JANUARY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-15-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 31-15-10; THEN DEVIATES TO THE SOUTHWEST BEFORE IT INTERSECTS THE SECTION LINE AND DEVIATES TO THE NORTH SIDE OF THE SECTION LINE; AND INTERSECTS THE SECTION LINE AT 2,103' EAST OF THE NORTHWEST CORNER OF SECTION 31-15-1-, THEN CONTINUES WEST ON THE SECTION LINE TO THE NORTHWEST CORNER OF SECTION 31-15-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 34-15-10 TO COMMENCE THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 137 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 134 TO 136 PETITIONED BY JULIUS HINES AND OTHERS FOR THE VACATION OF ALL THAT PORTION OF WHAT IS KNOWN AS THE "AMERICUS AND ALMA" ROAD RUNNING THROUGH TOWNSHIP 15, RANGE 10 AND RELOCATING THE SAME, [PACKET 385 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON

SEPTEMBER 10, 1881, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON OCTOBER 14, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 28-15-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-15-10 ON THE 3RD STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 229 DATED SEPTEMBER 21, 1881, FOR A ROAD SURVEY IN TOWNSHIP 15-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 28-15-10 ON THIS ROAD SURVEY

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-15-10 ON THE 3RD STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY

- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 177 DATED OCTOBER 10, 1879, FOR A COUNTY ROAD IN TOWNSHIP 15-10, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-15-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 31-15-10 AT AN ANGLE STONE IN THE ROAD SURVEY
- 2) THE ROAD EXTENDS EAST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-15-10 AT THE POINT OF COMMENCEMENT OF THIS ROAD SURVEY

- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER SIX IN SURVEY BOOK "E" ON PAGE 6 DATED FEBRUARY 18-20, 1884, A **PERMANENT SURVEY** TO SUBDIVIDE SECTION 28-15-10 FOR MARSTELLER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 28-15-10 ON THIS **PERMANENT SURVEY**. HIS SURVEY DRAWING SHOWS THAT THIS SECTION CORNER IS THE SOUTHEAST CORNER OF THE MARSTELLER TRACT. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 23 ON PAGE 183 IN THE REGISTER OF DEEDS OFFICE ON FEBRUARY 22, 1884, AND SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 15-10.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.01-1/2 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 28-15-10 AND THE NORTHEAST CORNER OF THE MARSTELLER TRACT
- 2) 80.03 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-15-10

- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 102, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGES 182 & 183 DATED DECEMBER 10, 1904 AT THE ORDER OF HUME, ET. AL. FOR THE

PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 29, THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 28, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 21, ALL IN TOWNSHIP 15 AND RANGE 10, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN POOR CONDITION** AT THE SOUTHEAST CORNER OF SECTION 28-15-10 ON THIS **PERMANENT SURVEY**. **HE RESET THE STONE AND HE MARKED A “+” ON THE TOP OF THE STONE**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 99 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET “M 101” IN MISCELLANEOUS DRAWER NUMBER 5 IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.96 CHAINS NORTH TO THE LOCATION FOR THE EAST 1/4 CORNER OF SECTION 28-15-10 AS MARKED BY THE **WITNESS STONE** MARKED “E 20” HE SET AT 20 FEET EAST AND THE **WITNESS STONE** MARKED “W 20” HE SET AT 20 FEET WEST OF THE TRUE POSITION
- 2) 79.93 CHAINS NORTH TO THE 12” X 8” X 5” STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 28-15-10
- 3) 99.99 CHAINS NORTH TO THE 18” X 12” X 4” STONE MARKED “1/8” HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 21-15-10
- 4) 120.05 CHAINS NORTH TO THE STONE THAT HE FOUND LYING ON TOP OF THE SURFACE AT THE WEST 1/4 CORNER OF SECTION 21-15-10. **HE RESET THIS STONE** AND HE PLACED A 24” X 12” X 3” STONE BESIDE THE STONE HE FOUND FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 21-15-10
- 5) 140.26 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 21-15-10
- 6) 160.45 CHAINS NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE
- 7) 40.18 CHAINS WEST TO THE STONE HE FOUND AT 6” UNDER THE SOIL AT THE SOUTH 1/4 CORNER OF SECTION 28-15-10. **HE RESET THIS STONE** IN THE SAME PLACE FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 28-15-10
- 8) 60.30 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 28-15-10
- 9) 80.42 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 28-15-10

NORTHWEST CORNER 34-15-10