

SOUTHWEST CORNER SECTION 34, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 2 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 11" X 2-1/2"** FOR THE CORNER TO SECTIONS 33 & 34-15-10 ON THE 3RD STANDARD PARALLEL ON OCTOBER 1, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 20" X 12" X 4" LIMESTONE THEY SET ON LEVEL GROUND FOR THE SOUTH 1/4 CORNER OF SECTION 34-15-10
 - 2) 80.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 31" X 13" X 3" LIMESTONE THEY SET ON A SOUTH SLOPE FOR THE CORNER TO SECTIONS 34 & 35-15-10
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 137 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 134 TO 136 PETITIONED BY JULIUS HINES AND OTHERS FOR THE VACATION OF ALL THAT PORTION OF WHAT IS KNOWN AS THE "AMERICUS AND ALMA" ROAD RUNNING THROUGH TOWNSHIP 15, RANGE 10 AND RELOCATING THE SAME, [PACKET 385 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 10, 1881, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON OCTOBER 14, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 33-15-10 ON THE 3RD STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 229 DATED SEPTEMBER 21, 1881, FOR A ROAD SURVEY IN TOWNSHIP 15-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 33-15-10 ON THE 3RD STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE TO COMMENCE THIS ROAD SURVEY
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 28 DATED AUGUST 23, 1882, FOR A ROAD SURVEY ON THE 3RD STANDARD PARALLEL IN TOWNSHIPS 15 & 16, RANGE 10 FOR R. EDEN, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-15-10 ON THE 3RD STANDARD PARALLEL AS HE RAN THE 3RD STANDARD PARALLEL FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 33-15-10 TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-16-10 ON THIS ROAD SURVEY. NO WIDTH IS RECORDED ON THIS ROAD SURVEY.

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, A ROAD SURVEY FOR ROAD NUMBER 137 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 334 TO 336 PETITIONED BY RICHARD EDEN AND OTHERS TO VACATE AND RELOCATE A COUNTY ROAD ON THE 3RD STANDARD PARALLEL BETWEEN

TOWNSHIPS 15-10 & 16-10 [PACKET 406 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 23, 1882, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 6, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 24, 1882 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-15-10 ON THE 3RD STANDARD PARALLEL TO BEGIN THIS ROAD SURVEY. THE ROAD VACATED WAS ALL THAT PART OF THE SANTA FE ROAD THOUGH SECTIONS 2, 3 & 4-16-10 TO THE EAST LINE OF SECTION 2-16-10.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS RELOCATED ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 33-15-10 TO COMMENCE THIS ROAD RELOCATION SURVEY
 - 2) THIS RELOCATED ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-16-10, THEN EXTENDS SOUTH ON THE EAST SIDE OF SECTION 2-16-10 TO INTERSECT THE ROAD AS ORIGINALLY ESTABLISHED AT THE TERMINUS OF THIS RELOCATED ROAD
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, ALONG WITH W. S. WHITLOCK, WABAUNSEE COUNTY SURVEYOR, IN SURVEY NUMBER 88, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 168 DATED DECEMBER 30, 1903 AT THE REQUEST OF M. W. LANGLEY, W. M. JOHNSON, W. W. PATTERSON, AND J. H. SMITH FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES AND SUBDIVISION OF SECTION 23 AND THE CORNERS AND BOUNDARIES OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 26, ALL IN TOWNSHIP 15 OF RANGE 10 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-15-10 ON THE 3RD STANDARD PARALLEL. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-15-10 TO ESTABLISH THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 14 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 156" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

SOUTHWEST CORNER 34-15-10