

**SOUTH 1/4 CORNER SECTION 35, TOWNSHIP 15 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 3 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 9" X 4"** ON A GENTLE SLOPE TO THE SOUTHEAST FOR THE SOUTH 1/4 CORNER OF SECTION 35-15-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON OCTOBER 2, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 31" X 13" X 3" LIMESTONE THEY SET ON A SOUTH SLOPE FOR THE CORNER TO SECTIONS 34 & 35-15-10
- 2) 40.00 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 28" X 11" X 3" LIMESTONE THEY SET ON A NORTHEAST SLOPE FOR THE CORNER TO SECTIONS 35 & 36-15-10

- 2) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 56, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 54 DATED JUNE 20, 1870 TO ESTABLISH THE 1/4 CORNER ON THE SOUTH LINE AND ALSO THE CENTER OF SECTION 35-15-10, SAID THAT **HE SET A LIMESTONE** FOR THE SOUTH 1/4 CORNER OF SECTION 35-15-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-15-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-10. A NOTE ON THE LEFT PAGE SAID "SEE 66".

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.90-1/2 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-15-10
- 2) 39.90-1/2 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-10
- 3) 79.94 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35-15-10

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 13, 2011 FOR PROJECT NUMBER 11130-02, A SURVEY FOR KIT DETWILER IN THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 35, SURVEY F35002 IN THE SURVEY FILE FOR TOWNSHIP 15-10, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 35-15-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL. **HE FOUND A 4" X 12" X 14" LIMESTONE** AT THE SOUTH 1/4 CORNER OF SECTION 35-15-10 THAT WAS SET BY S. DAVIES, DEPUTY COUNTY SURVEYOR, IN 1870, AS RECORDED IN SURVEY BOOK "B" ON PAGE 54.

- 1) 1/2" X 18" REBAR WITH HIS "LS 752" CAP SET ON THE SOUTH SIDE CENTER OF THE STONE
- 2) SICKLE GUARD ON THE NORTH SIDE CENTER BOTTOM OF THE STONE
- 3) 1.5' NORTH TO THE TRAVELED WAY OF GRAVEL ROAD 370 EAST-WEST
- 4) 43.8' SW TO A CONCRETE NAIL & WASHER IN THE EAST SIDE OF A FENCE POST
- 5) 33.05' NW TO THE SW CORNER OF A 3" SQUARE PIPE CORNER FENCE POST
- 6) 27' NORTH TO A PIPE FENCE EAST-WEST
- 7) 18.7' WEST TO A PIPE FENCE TO THE NORTH
- 8) 17.15' SOUTH TO A WIRE FENCE EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 25.0' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET ON THE RIGHT-OF-WAY LINE
- 2) 850.00' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST TRACT CORNER
- 3) 5,290.71' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 35-15-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 2,643.23' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-15-10

SOUTH QUARTER CORNER 35-15-10