

SOUTHWEST CORNER SECTION 35, TOWNSHIP 15 SOUTH, RANGE 10 EAST

- 1) ON PAGE 3 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 31" X 13" X 3"** ON THE SOUTH SLOPE FOR THE CORNER TO SECTIONS 34 & 35-15-10 ON THE 3RD STANDARD PARALLEL ON OCTOBER 2, 1855.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 22" X 9" X 4" LIMESTONE THEY SET ON A GENTLE SLOPE TO THE SOUTHEAST FOR THE SOUTH 1/4 CORNER OF SECTION 35-15-10
 - 2) 80.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 28" X 11" X 3" LIMESTONE THEY SET ON A NORTHEAST SLOPE FOR THE CORNER TO SECTIONS 35 & 36-15-10

- 2) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 56, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 54 DATED JUNE 20, 1870 TO ESTABLISH THE SOUTH 1/4 CORNER ON THE SOUTH LINE AND ALSO THE CENTER OF SECTION 35-15-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. A NOTE ON THE LEFT PAGE SAID "SEE 66".
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.90-1/2 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE LIMESTONE THAT HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 35-15-10
 - 2) 79.81 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-10

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 28 DATED AUGUST 23, 1882, FOR A ROAD SURVEY ON THE 3RD STANDARD PARALLEL IN TOWNSHIPS 15 & 16, RANGE 10 FOR R. EDEN, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL AS HE RAN THE 3RD STANDARD PARALLEL FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 33-15-10 TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-16-10 ON THIS ROAD SURVEY. NO WIDTH IS RECORDED ON THIS ROAD SURVEY.

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, A ROAD SURVEY FOR ROAD NUMBER 137 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 334 TO 336 PETITIONED BY RICHARD EDEN AND OTHERS TO VACATE AND RELOCATE A COUNTY ROAD ON THE 3RD STANDARD PARALLEL BETWEEN TOWNSHIPS 15-10 & 16-10 [PACKET 406 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 23, 1882, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 6, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 24, 1882 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL TO BEGIN THIS ROAD SURVEY. THE ROAD VACATED WAS ALL THAT PART OF THE SANTA FE ROAD THOUGH SECTIONS 2, 3 & 4-16-10 TO THE EAST LINE OF SECTION 2-16-10.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS RELOCATED ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 33-15-10 TO COMMENCE THIS ROAD RELOCATION SURVEY
 - 2) THIS RELOCATED ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-16-10, THEN

EXTENDS SOUTH ON THE EAST SIDE OF SECTION 2-16-10 TO INTERSECT THE ROAD AS ORIGINALLY ESTABLISHED AT THE TERMINUS OF THIS RELOCATED ROAD

- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 440 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 25 THROUGH 28 PETITIONED BY L. N. GIBSON AND OTHERS FOR THE LOCATION OF TWO ROADS IN TOWNSHIPS 15-10 AND 16-10 AND THE VACATION OF TWO ROADS IN TOWNSHIP 16-10 [PACKET 677 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 21, 1898, WERE ESTABLISHED AS 40 FOOT WIDE ROADS, LAYING 20 FEET EACH SIDE OF THE LINE DESCRIBED AND MARKED, ON APRIL 21, 1898 AS NOTED BY JACOB JACOB, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED TO BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON JANUARY 7, 1900 BY MATTHEW BROWN, COUNTY SURVEYOR, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL ON THE SECOND ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECOND ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 23-15-10 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS SECOND ROAD ON THIS ROAD SURVEY
- 2) THIS SECOND ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 2-16-10, THEN SOUTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 11-16-10
- 3) SEE THE ROAD SURVEY FOR THE REMAINDER OF THE ROAD AS IT GOES THROUGH A SERIES OF ANGLES UNTIL THE END OF THIS ROAD AT THE INTERSECTION WITH THE FIRST ROAD ON THIS ROAD SURVEY

- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 88, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 168 DATED DECEMBER 30, 1903 AT THE REQUEST OF M. W. LANGLEY AND OTHERS, SAID THAT HE DID **NOT** FIND THE STONE AT THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL. HE DID DETERMINE A **CALCULATED POSITION** FOR THIS CORNER ON THE 3RD STANDARD PARALLEL BASED ON THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-15-10 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 14 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 156" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 0.42 CHAINS NORTH TO THE ROAD STONE HE FOUND MARKED "3M" ON THE NORTH SIDE
- 2) 40.09 CHAINS NORTH TO THE LOCATION FOR THE WEST 1/4 CORNER OF SECTION 35-15-10
- 3) 80.18 CHAINS NORTH TO THE LOCATION FOR THE NORTHWEST CORNER OF SECTION 35-15-10
- 4) 120.27 CHAINS NORTH TO THE FLAG HE SET FOR THE WEST 1/4 CORNER OF SECTION 26-15-10
- 5) 140.31-1/2 CHAINS NORTH TO THE FLAG HE SET FOR THE WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 26-15-10
- 6) 160.36 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 26-15-10

CONTINUED ON PAGE 3

- 7) IN GREEN DIETZGEN FIELD BOOK NUMBER 14 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE LABELED "JACOBS CREEK BRIDGE" ON PAGE 24 IT SHOWS AN **IRON PIN** AT THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL IN APRIL 1934. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THERE IS NO RECORD OF THE ORIGIN OF THIS IRON PIN AND IT MAY HAVE BEEN "HEELED-IN" FOR THIS BRIDGE PROJECT!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-10 SHOWS AN **IRON PIN** AT THE "SW CORNER SECTION 35-15-10" ON THE 3RD STANDARD PARALLEL. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THERE IS NO RECORD OF THE ORIGIN OF THIS IRON PIN!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 29' NW TO AN IRON PIN
 - 2) 38.8' NE TO AN IRON PIN
- 9) KRETSINGER TIE BOOK NUMBER 13 ON PAGE 40 AT THE BOTTOM OF THE PAGE SHOWS A **1/2" SQUARE IRON PIN** AT THE "SW CORNER SECTION 35-15-10" ON THE 3RD STANDARD PARALLEL. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THERE IS NO RECORD OF THE ORIGIN OF THIS IRON PIN!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 29.0' NW TO A 1/2" SQUARE IRON PIN
 - 2) 38.8' NE TO A 1/2" SQUARE IRON PIN
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 13, 2011 FOR PROJECT NUMBER 11130-02, A SURVEY FOR KIT DETWILER IN THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 35, SURVEY F35002 IN THE SURVEY FILE FOR TOWNSHIP 15-10, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THE 3RD STANDARD PARALLEL, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS BOTH **LOST** AND **OBLITERATED**. HE DID **NOT** RESET THE SOUTHWEST CORNER OF SECTION 35-15-10 ON THIS SURVEY.
 - 1) **29.0' NW TO A FOUND 1/2" SQUARE IRON WITNESS PIN** ATTRIBUTABLE TO W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER FROM 1952 TO 1981, FROM HIS NOTES.

SOUTHWEST CORNER 35-15-10