

**WEST 1/16 CORNER SOUTHWEST QUARTER SECTION 20, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, FOR R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 72, AN **AGREEMENT SURVEY** FOR GEORGE MOSS AND GEORGE W. GORMAN TO SURVEY AND SUBDIVIDE PARTS OF SECTIONS 19, 20 30 & 31 IN TOWNSHIP 15, RANGE 11 RECORDED IN SURVEY BOOK "E" ON PAGE 72 BUT NOT DATED, SAID THAT **HE SET A TRIANGULAR LIMESTONE MARKED "1/8" THAT MEASURES 3" AT THE TOP, 15" TALL, AND 10" AT THE BASE** FOR THE EAST 1/8<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 19-15-11 ON THIS **AGREEMENT SURVEY**. THIS SURVEY WAS RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 25 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 WITH THE NOTATION THAT IT WAS SURVEYED OCTOBER 27 & 28 AND NOVEMBER 6-8, 1884, WITH A COPY OF THIS SURVEY FILED AS SURVEY F19001 IN THE SURVEY FILE FOR TOWNSHIP 15-11.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,320' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-15-11
  - 2) 1,319.5' NORTH TO THE 8" X 16" X 4" TRIANGULAR LIMESTONE HE SET FOR THE EAST 1/4 CORNER OF SECTION 19-15-11
  - 3) 2,639.5' NORTH TO THE 10" X 15" X 3" TRIANGULAR LIMESTONE HE SET FOR THE EAST 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 19-15-11
  - 4) 3,959' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE
  - 5) 1,320' WEST TO THE 12" X 16" X 3" TRIANGULAR LIMESTONE HE SET FOR THE CENTER OF THE SE1/4 OF SECTION 19-15-11
  - 6) 2,640' WEST TO THE 12" X 16" X 3" TRIANGULAR LIMESTONE HE SET FOR THE EAST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 19-15-11
  - 7) 3,690' WEST TO THE 12" X 16" X 3" TRIANGULAR LIMESTONE HE SET FOR THE CENTER OF THE SW1/4 OF SECTION 19-15-11
  - 8) 5,319' WEST TO THE 3" X 18" X 12" LIMESTONE THAT WAS POINTED ON TOP HE SET FOR THE WEST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 19-15-11 ON THE RANGE LINE
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 117, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 198 DATED MAY 28, 1905 FOR L. N. NANCE, PRINCIPAL PETITIONER FOR A ROAD ON THE LYON AND WABAUNSEE COUNTY LINE IN TOWNSHIP 15, RANGES 10 & 11, SAID THAT **HE AND WABAUNSEE COUNTY SURVEYOR W. S. WHITLOCK FOUND THE STONE UNDER A FENCE** AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 19-15-11 ON THIS ROAD SURVEY ON THE COUNTY LINE. THEY USED THIS STONE, THE STONE THAT THEY FOUND AT THE EAST 1/8<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 19-15-11, THE STONE THAT THEY FOUND AT THE WEST 1/4 CORNER OF SECTION 17-15-11, AND THE STONE THAT THEY FOUND AT THE NORTHWEST CORNER OF SECTION 17-15-11 TO SET A 20" X 14" X 2" STONE FOR THE NORTHEAST CORNER OF SECTION 19-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE ON THIS ROAD SURVEY.
- HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:**
- 1) 40.08 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 19-15-11
  - 2) 60.10 CHAINS NORTH TO THE 20" X 14" X 2" STONE HE SET FOR THE NORTHEAST CORNER OF SECTION 19-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE
  - 3) 100.14 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 18-15-11 IN WABAUNSEE COUNTY

- 4) 140.20 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 18 IN WABAUNSEE COUNTY
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 597 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 257 THROUGH 260 PETITIONED BY L. N. NANCE AND OTHERS FOR A ROAD ON THE LYON AND WABAUNSEE COUNTY LINE IN TOWNSHIPS 15-10 AND 15-11 [PACKET 744 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 28, 1905, WAS GRANTED AS A 50 FOOT WIDE ROAD, 25 FEET EACH SIDE OF THE COUNTY LINE, ON APRIL 6, 1905 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND ATTESTED BY W. F. EGGERS, COUNTY CLERK, SAID THAT **HE AND WABAUNSEE COUNTY SURVEYOR W. S. WHITLOCK FOUND THE STONE** FOR THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 19-15-11 ON THIS ROAD SURVEY ON THE COUNTY LINE. THEY USED THIS STONE, THE STONE THAT THEY FOUND AT THE EAST 1/8<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 19-15-11, THE STONE THAT THEY FOUND AT THE WEST 1/4 CORNER OF SECTION 17-15-11, AND THE STONE THAT THEY FOUND AT THE NORTHWEST CORNER OF SECTION 17-15-11 TO SET A 20" X 14" X 2" STONE FOR THE NORTHEAST CORNER OF SECTION 19-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE ON THIS ROAD SURVEY. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.08 CHAINS NORTH TO THE STONE THEY FOUND AT THE EAST 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 19-15-11
  - 2) 60.10 CHAINS NORTH TO THE 20" X 14" X 2" STONE THEY SET FOR THE NORTHEAST CORNER OF SECTION 19-15-11 ON THE COUNTY LINE
  - 3) 100.14 CHAINS NORTH TO THE STONE THEY FOUND AT THE WEST 1/4 CORNER OF SECTION 17-15-11 IN WABAUNSEE COUNTY
  - 4) 140.20 CHAINS NORTH TO THE STONE THEY FOUND AT THE NORTHWEST CORNER OF SECTION 17-15-11 IN WABAUNSEE COUNTY

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 20-15-11