

NORTHWEST CORNER SECTION 22, TOWNSHIP 15 SOUTH, RANGE 11 EAST

- 1) ON PAGE 278 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 35" X 15" X 2"** FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-15-11 ON THE COUNTY LINE.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.04 CHAINS EAST ON THE COUNTY LINE TO THE 24" X 10" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-15-11
 - 2) 80.08 CHAINS EAST ON THE COUNTY LINE TO THE 24" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-15-11

- 2) IN A SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 188 DATED JUNE 23 TO 29, 1949, AND WITH "L. M. GOULD SURVEYOR" [LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978] WRITTEN IN PENCIL, IT SHOWS THAT **HE SET AN IRON PIN** FOR THE NORTHWEST CORNER OF SECTION 22-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE ON THIS SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 5,349' WEST ON THE COUNTY LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 21-15-11
 - 2) 7,243' WEST ON THE COUNTY LINE TO THE STONE HE FOUND ON THE KANSAS INDIAN RESERVE LINE ON THE NORTH SIDE OF THE NE1/4 OF SECTION 20-15-11
 - 3) 2,662' EAST ON THE COUNTY LINE TO THE STONE AND IRON PIPE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 22-15-11
 - 4) 5,313' EAST ON THE COUNTY LINE TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF SECTION 22-15-11
 - 5) 10,585.1' EAST ON THE COUNTY LINE TO AN IRON PIN HE SET FOR THE NORTHEAST CORNER OF SECTION 23-15-11, AT 30' EAST OF AN OLD STONE WALL, WHICH WAS A REFERENCE TO THE ORIGINAL SECTION CORNER ACCORDING TO THE SURVEY OF ALVA J. SMITH RECORDED IN SURVEY BOOK "F" ON PAGE 179 (SURVEY #99) IN 1905

- 3) THE KRETSINGER TIE BOOK FOR TOWNSHIP 15-11 SHOWS AN **IRON PIN** AT THE "NE CORNER SECTION 21-15-11" AND "NW CORNER SECTION 22-15-11" ON THE LYON AND WABAUNSEE COUNTY LINE, BUT GIVES NO REFERENCES ON EITHER PAGE.

NORTHWEST CORNER 22-15-11