

NORTH 1/4 CORNER SECTION 25, TOWNSHIP 15 SOUTH, RANGE 11 EAST

- 1) ON PAGE 273 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 24 & 25-15-11.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.04 CHAINS WEST TO THE 18" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-15-11
 - 2) 40.04 CHAINS EAST TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 24 & 25-15-11 ON THE EAST TOWNSHIP BOUNDARY

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 92, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 172 DATED APRIL 12, 1904 AT THE REQUEST OF E. W. CHANDON FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHWEST CORNER, THE SOUTH 1/4 CORNER, AND THE SOUTHEAST CORNER OF SECTION 24-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET AN 18" X 12" X 3" STONE** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 24-15-11 ON A TRANSIT LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 24-15-11 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 34 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 155" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.98-1/4 CHAINS EAST TO THE 18" X 6" X 5" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SEC. 24-15-11
 - 2) 39.96-1/2 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-11 ON THE RANGE LINE, WITH FENCE POSTS STANDING AT 56 LINKS SOUTHEAST, 47 LINKS NORTHEAST, 50 LINKS NORTHWEST, AND 47 LINKS SOUTHWEST
 - 3) 19.98-1/4 CHAINS WEST TO THE 20" X 8" X 4" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SEC. 24-15-11
 - 4) 39.96-1/2 CHAINS WEST TO THE 27" X 12" X 3" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 24-15-11, AT 30 FEET SOUTH AND 30 FEET EAST OF THE CORNER OF A STONE WALL
 - 5) 79.85-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 23-15-11

NORTH QUARTER CORNER 25-15-11