

**NORTH 1/16 CORNER NORTHEAST QUARTER SECTION 25, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 92, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 172 DATED APRIL 12, 1904 AT THE REQUEST OF E. W. CHANDON FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHWEST CORNER, THE SOUTH 1/4 CORNER, AND THE SOUTHEAST CORNER OF SECTION 24-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET AN 18" X 6" X 5" STONE** FOR THE PERMANENT SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 24-15-11 ON A TRANSIT LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 24-15-11 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 34 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 155" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 19.98-1/4 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-11, WITH FENCE POSTS STANDING AT 56 LINKS SOUTHEAST, 47 LINKS NORTHEAST, 50 LINKS NORTHWEST, AND 47 LINKS SOUTHWEST
- 2) 19.98-1/4 CHAINS WEST TO THE 18" X 12" X 3" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 24-15-11
- 3) 39.94 CHAINS WEST TO THE 20" X 8" X 4" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 24-15-11
- 4) 59.94-3/4 CHAINS WEST TO THE 27" X 12" X 3" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 24-15-11, AT 30 FEET SOUTH AND 30 FEET EAST OF THE CORNER OF A STONE WALL
- 5) 99.83-3/4 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 23-15-11

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 25-15-11