

NORTHWEST CORNER SECTION 25, TOWNSHIP 15 SOUTH, RANGE 11 EAST

- 1) ON PAGE 273 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 10" X 5"** FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-15-11.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.04 CHAINS EAST TO THE 22" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 24 & 25-15-11
 - 2) 80.08 CHAINS EAST TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 24 & 25-15-11 ON THE EAST TOWNSHIP BOUNDARY
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 230 & 231 FOR A PETITION BY D. S. AVERY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-11, 16-11 AND 17-11 [PACKET 190 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 21 THROUGH 24, 1875, AND WAS ESTABLISHED ON JANUARY 3, 1876 AS A 50 FOOT WIDE ROAD. APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 26-15-11 ON THIS ROAD SURVEY. HE NOTED THAT THE TOTAL LENGTH OF THIS ROAD IS "11 MILES, 41 CHAINS, 5 RODS AND 7-1/2 FEET".

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE TO THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 36-15-11 ON THE 3RD STANDARD PARALLEL AT A TURN TO THE SOUTHWESTERLY TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AND THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 15-17-11 TO THE TERMINUS OF THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 48 DATED MARCH 1883, FOR A ROAD IN TOWNSHIP 15 AND RANGES 11 & 12 FOR J. M. BUTLER, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 25-15-11 ON THIS ROAD SURVEY FOR A 60 FOOT WIDE ROAD, **EXCEPT** AS STATED IN HIS SURVEY NOTES.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-15-11 TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 2 MILES AND 54 RODS TO AN ANGLE STONE HE SET FOR A DEVIATION TO THE NORTH, AND INTERSECTS THE SECTION LINE AT AN ANGLE STONE HE SET AT 158 FEET WEST OF THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 20-15-12 AND THEN CONTINUES EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-15-12 TO THE TERMINUS OF THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 206 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 410 TO 412 PETITION BY JAMES M. BUTLER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-11 AND 15-12 [PACKET 451 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 31, 1883 AND WAS ORDERED ESTABLISHED AS A 60 FOOT WIDE ROAD ALLOWED "FROM THE NORTHWEST CORNER OF SECTION 27-15-11 TO THE NORTHEAST CORNER OF SECTION 30-15-12" ONLY BY J. E. JONES, CHAIRMAN OF THE BOARD OF COUNTY

COMMISSIONERS, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 25-15-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE ALLOWED ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-15-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THE ALLOWED ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-15-12 TO THE TERMINUS OF THIS ROAD SURVEY
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 92, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 172 DATED APRIL 12, 1904 AT THE REQUEST OF E. W. CHANDOIN FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHWEST CORNER, THE SOUTH 1/4 CORNER, AND THE SOUTHEAST CORNER OF SECTION 24-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 27" X 12" X 3" STONE AT 30 FEET SOUTH AND 30 FEET EAST OF THE CORNER OF A STONE WALL** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 24-15-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 34 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 155" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.89 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 23-15-11
- 2) 40.27 CHAINS NORTH TO THE 15" X 9" X 3" STONE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 23-15-11
- 3) 80.54 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE
- 4) 80.54 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-15-11 ON LINE WITH A FENCE TO THE WEST
- 5) 19.98-1/4 CHAINS EAST TO THE 20" X 8" X 4" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SEC. 24-15-11
- 6) 39.96-1/2 CHAINS EAST TO THE 18" X 12" X 3" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 24-15-11
- 7) 59.94-3/4 CHAINS EAST TO THE 18" X 6" X 5" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SEC. 24-15-11
- 8) 79.93 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-11 ON THE RANGE LINE, WITH FENCE POSTS STANDING AT 56 LINKS SOUTHEAST, 47 LINKS NORTHEAST, 40 LINKS NORTHWEST AND 47 LINKS SOUTHWEST

NORTHWEST CORNER 25-15-11