

**WEST 1/4 CORNER SECTION 25, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 273 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 8" X 3-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 26-15-11.
  
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 92, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 172 DATED APRIL 12, 1904 AT THE REQUEST OF E. W. CHANDON FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHWEST CORNER, THE SOUTH 1/4 CORNER, AND THE SOUTHEAST CORNER OF SECTION 24-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 26-15-11 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-15-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 34 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 155" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

WEST QUARTER CORNER 25-15-11