

NORTHWEST CORNER SECTION 26, TOWNSHIP 15 SOUTH, RANGE 11 EAST

- 1) ON PAGE 275 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 5"** FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-15-11.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.41 CHAINS EAST TO THE 22" X 8" X 4-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-15-11
 - 2) 79.82 CHAINS EAST TO THE 22" X 8" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-15-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 48 DATED MARCH 1883, FOR A ROAD IN TOWNSHIP 15 AND RANGES 11 & 12 FOR J. M. BUTLER, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 26-15-11 ON THIS ROAD SURVEY FOR A 60 FOOT WIDE ROAD, EXCEPT AS STATED IN HIS SURVEY NOTES.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-15-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 3 MILES AND 54 RODS TO AN ANGLE STONE HE SET FOR A DEVIATION TO THE NORTH, AND INTERSECTS THE SECTION LINE AT AN ANGLE STONE HE SET AT 158 FEET WEST OF THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 20-15-12 AND THEN CONTINUES EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-15-12 TO THE TERMINUS OF THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 206 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 410 TO 412 PETITION BY JAMES M. BUTLER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-11 AND 15-12 [PACKET 451 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 31, 1883 AND WAS ORDERED ESTABLISHED AS A 60 FOOT WIDE ROAD ALLOWED "FROM THE NORTHWEST CORNER OF SECTION 27-15-11 TO THE NORTHEAST CORNER OF SECTION 30-15-12" ONLY BY J. E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 26-15-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE ALLOWED ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-15-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THE ALLOWED ROAD EXTENDS EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-15-12 TO THE TERMINUS OF THIS ROAD SURVEY

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 92, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 172 DATED APRIL 12, 1904 AT THE REQUEST OF E. W. CHANDON FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHWEST CORNER, THE SOUTH 1/4 CORNER, AND THE SOUTHEAST CORNER OF SECTION 24-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE AT 30 FEET SOUTH OF A WALL** AT THE SOUTHWEST CORNER OF SECTION 23-15-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 34 IN THE "KRETSINGER

COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 155" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 99, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 179 DATED OCTOBER 4, 1904, FOR A ROAD IN TOWNSHIP 15-11 FOR G. E. GORMAN, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE AT 30 FEET SOUTH OF A STONE WALL** AT THE NORTHWEST CORNER OF SECTION 26-15-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 80.63 CHAINS TO THE 22" X 9" X 3" STONE MARKED "R" ON THE SOUTH SIDE HE SET FOR THE NORTHWEST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
- 2) 201.53 CHAINS NORTH TO THE STONE HE FOUND LOOSE ON THE GROUND AT THE EAST 1/4 CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
- 3) 24190 CHAIN NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
- 4) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 80 CHAINS BY GOVERNMENT SURVEY TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-15-11; THEN CONTINUES SOUTH ON THE SECTION LINES FOR 40.15 CHAINS TO THE GOVERNMENT STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 35-15-11; THEN CONTINUES SOUTH ON THE SECTION LINES FOR 40.15 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-15-11 ON THE 3RD STANDARD PARALLEL TO BEGIN THIS ROAD SURVEY

- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 590 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 229 THROUGH 232 PETITIONED BY G. E. GORMAN AND OTHERS FOR A ROAD IN TOWNSHIP 15-11 [PACKET 736 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEY ON OCTOBER 5, 1904, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, 25 FEET EACH SIDE OF THE SECTION LINE, ON OCTOBER 6, 1904 AS NOTED BY JOHN LONGLEY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON OCTOBER 12, 1904 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE ON AT 30 FEET SOUTH OF A STONE WALL** AT THE NORTHWEST CORNER OF SECTION 26-15-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 80.63 CHAINS TO THE 22" X 9" X 3" STONE MARKED "R" ON THE SOUTH SIDE HE SET FOR THE NORTHWEST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
- 2) 201.53 CHAINS NORTH TO THE STONE HE FOUND LOOSE ON THE GROUND AT THE EAST 1/4 CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
- 3) 24190 CHAIN NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
- 4) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 80 CHAINS BY GOVERNMENT SURVEY TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-15-11; THEN CONTINUES SOUTH ON THE SECTION LINES FOR 40.15 CHAINS TO THE GOVERNMENT STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 35-15-11; THEN CONTINUES SOUTH ON THE SECTION LINES FOR 40.15 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-15-11 ON THE 3RD STANDARD PARALLEL TO BEGIN THIS ROAD SURVEY

- 7) IN A SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 188 DATED JUNE 23 TO 29, 1949, AND WITH "L. M. GOULD SURVEYOR" [LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978] WRITTEN IN PENCIL, IT SHOWS THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 26-15-11 ON THIS SURVEY. HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,321.6' NORTH TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF SECTION 22-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE
 - 2) 2,638' WEST TO THE IRON PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 22-15-11
 - 3) 5,276' WEST TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF SECTION 22-15-11
 - 4) 10,598' WEST TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF SECTION 21-15-11
 - 5) 15,889' WEST TO THE "CENTER OF THE COUNTY ROAD AT THE SECTION CORNER" AT THE SOUTHWEST CORNER OF SECTION 20-20-11
- 8) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 66 AT THE TOP OF THE PAGE SHOWS A **STONE** AT THE "NE CORNER SECTION 27-15-11".
- 1) 46.0' NW TO AN IRON PIN ALONG A ROCK WALL
 - 2) 30' NORTH TO A ROCK WALL EAST AND WEST-EXTENDED
 - 3) SEE THE DRAWING
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-11 SHOWS A **STONE** AT THE "SE CORNER SECTION 22-15-11".
- 1) 49.3' NE TO A 1/2" SQUARE IRON PIN
 - 2) 42.6' SE TO A 1/2" SQUARE IRON PIN [DISTURBED]
 - 3) 46.8' NW TO A 1/2" SQUARE IRON PIN
- 10) IN A FIELD BOOK LABELED ""MJH MISC. 1965-1967" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE ON PAGE 46 FOR THE "LEAVELL PROPERTY DIVISION" IT SHOWS THAT **THEY FOUND THE STONE** AT THE "NORTHWEST CORNER OF THE NW 1/4 OF SECTION 26-16-11".
- 1) 46.8' NW TO A REBAR
 - 2) 49.3' NE TO A REBAR

NORTHWEST CORNER 26-15-11