

WEST 1/4 CORNER SECTION 26, TOWNSHIP 15 SOUTH, RANGE 11 EAST

- 1) ON PAGE 275 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 27-15-11.
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 179 AND DATED OCTOBER 1904, SAID THAT HE DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 26-15-11 ON THIS ROAD SURVEY.
- 3) IN A FIELD BOOK LABELED "MJH MISC. 1965-1967" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE ON PAGE 46 FOR THE "LEAVELL PROPERTY DIVISION" IT SHOWS A **REBAR** AT THE SOUTHWEST CORNER OF THE NW 1/4 OF SECTION 26-15-11. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING THIS REBAR AS THERE IS NO RECORD OF THE ORIGIN OF THIS REBAR!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 35.25' NORTH OF WEST TO A SPIKE IN THE TOP OF A CORNER FENCE POST
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-11 SHOWS A **REBAR** AT THE "W1/4 CORNER SECTION 26-15-11". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING THIS REBAR AS THERE IS NO RECORD OF THE ORIGIN OF THIS REBAR!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 35.25' NORTH OF WEST TO A SPIKE IN THE TOP OF A CORNER FENCE POST

WEST QUARTER CORNER 26-15-11