

**NORTHWEST CORNER SECTION 27, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 277 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 32" X 12" X 4"** FOR THE CORNER TO SECTIONS 21, 22, 27 & 28-15-11.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 39.97 CHAINS EAST TO THE 24" X 8" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 27-15-11
  - 2) 79.94 CHAINS EAST TO THE 18" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-15-11
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 48 DATED MARCH 1883, FOR A ROAD IN TOWNSHIP 15 AND RANGES 11 & 12 FOR J. M. BUTLER, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 27-15-11 TO BEGIN THIS ROAD SURVEY FOR A 60 FOOT WIDE ROAD, EXCEPT AS STATED IN HIS SURVEY NOTES.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 4 MILES AND 54 RODS TO AN ANGLE STONE HE SET FOR A DEVIATION TO THE NORTH, AND INTERSECTS THE SECTION LINE AT AN ANGLE STONE HE SET AT 158 FEET WEST OF THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 20-15-12 AND THEN CONTINUES EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-15-12 TO THE TERMINUS OF THIS ROAD SURVEY
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 48 DATED MARCH 13, 1883 FOR A ROAD IN TOWNSHIP 15, RANGES 11 & 12 FOR J. M. BUTLER, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 27-15-11 TO BEGIN THIS ROAD SURVEY FOR A 60 FOOT WIDE ROAD.
  
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 206 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 410 TO 412 PETITION BY JAMES M. BUTLER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-11 AND 15-12 [PACKET 451 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 31, 1883 AND WAS ORDERED ESTABLISHED AS A 60 FOOT WIDE ROAD ALLOWED "FROM THE NORTHWEST CORNER OF SECTION 27-15-11 TO THE NORTHEAST CORNER OF SECTION 30-15-12" ONLY BY J. E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 27-15-11 TO COMMENCE THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THE ALLOWED ROAD EXTENDS EAST ON THE SECTION LINES FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-15-12 TO THE TERMINUS OF THIS ROAD SURVEY
  
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "C" ON PAGES 226 & 227 FOR ROAD NUMBER 319 ON A PETITION BY G. W. GORMAN [PACKET 580 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED JANUARY 1886, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 21-15-11 TO THE TERMINUS OF THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINED FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-10 ON THE RANGE LINE, THEN S. 71°40' W. FOR 215 FEET TO AN ANGLE STONE HE SET; THEN N. 71°15' W. FOR 722 FEET TO INTERSECT THE SECTION LINES AT A STONE HE SET AT 902 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 24-15-10; THEN CONTINUES WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 22-21-10 TO BEGIN THIS ROAD SURVEY
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD 319 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 226 TO 228 PETITIONED BY G. W. GORMAN AND OTHERS FOR THE VACATION AND LOCATION OF A COUNTY ROAD IN TOWNSHIPS 15-10 AND 15-11 [PACKET 580 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 2, 1885, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON APRIL 15, 1886 BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 5, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 21-15-11 TO END THIS ROAD SURVEY. THE ROAD TO BE VACATED WAS PETITIONED AS COMMENCING AT THE EAST CENTER OF SECTION 30-15-11, THENCE RUNNING WEST TWO MILES TO THE CENTER OF THE WEST SIDE OF SECTION 25-15-10 KNOWN AS THE THEODORE HOELLING ROAD. A PENCIL NOTE UNDER THE DRAWING ON PAGE 227 NOTED: THE PORTION OF THE PETITION ASKING FOR THE VACATION OF THE ROAD IN THE CENTER OF SECTIONS 25-15-10 AND 30-15-11 WAS **REJECTED**. THE ROAD WAS **NOT** VACATED – SEE COMMISSIONERS JOURNAL NUMBER 4 DATED JANUARY 14, 1886.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINED FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-10 ON THE RANGE LINE, THEN S. 71°40' W. FOR 215 FEET TO AN ANGLE STONE HE SET; THEN N. 71°15' W. FOR 722 FEET TO INTERSECT THE SECTION LINES AT A STONE HE SET AT 902 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 24-15-10; THEN CONTINUES WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 22-21-10 TO BEGIN THIS ROAD SURVEY
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 99, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 179 DATED OCTOBER 4, 1904, FOR G. E. GORMAN, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 22-15-11 ON THIS ROAD SURVEY. HE SAID THAT THIS PORTION OF THE ROAD SURVEY WAS MADE WITH THE WABAUNSEE COUNTY SURVEYOR.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 201.53 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
  - 2) 241.90 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "D" ON PAGES 229 THROUGH 232 FOR ROAD NUMBER 590 BY A PETITION BY G. E. GORMAN [PACKET 736 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED OCTOBER 1904, SAID THAT **HE FOUND THE STONE AT 30 FEET SOUTH OF A STONE WALL** AT THE NORTHWEST CORNER OF SECTION 26-15-11 ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD. HE SAID THAT THIS PORTION OF THE ROAD SURVEY WAS MADE WITH THE WABAUNSEE COUNTY SURVEYOR.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 201.53 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
  - 2) 241.90 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-11 SHOWS A **STONE** AT THE “SE CORNER SECTION 22-15-11”.
- 1) 45.5’ NW TO A 6 PR F C POST
  - 2) 30’ NORTH TO THE FACE OF A ROCK WALL
  - 3) 46.5’ NE TO THE TOP OF A CORNER FENCE POST
- 10) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-11 SHOWS A **STONE** AT THE “SE CORNER SECTION 22-15-11”.
- 1) 49.3’ NE TO A 1/2” SQUARE IRON PIN
  - 2) 42.6’ SE TO A 1/2’ SQUARE IRON PIN [DISTURBED]
  - 3) 46.8’ NW TO A 1/2” SQUARE IRON PIN
- 11) IN A SURVEY RECORDED IN SURVEY BOOK “D” ON PAGE 188 DATED JUNE 23 TO 29, 1949, AND WITH “L. M. GOULD SURVEYOR” [LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978] WRITTEN IN PENCIL, IT SHOWS THAT **HE SET AN IRON PIN** FOR THE SOUTHWEST CORNER OF SECTION 22-15-11 ON THIS SURVEY. THERE IS NO INDICATION OF THE METHODOLOGY HE USED TO SET THIS IRON PIN. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING THIS IRON PIN!!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,638’ EAST TO THE IRON PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 22-15-11 22
- 2) 5,276’ EAST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-15-11
- 3) 5,322’ WEST TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF SECTION 21-15-11
- 4) 10,613’ WEST TO THE CENTER OF THE COUNTY ROAD AT THE “SECTION CORNER” AT THE SOUTHWEST CORNER OF SECTION 20-15-11 – NO MONUMENT IDENTIFIED

NORTHWEST CORNER 27-15-11