

CENTER CORNER OF SECTION 29, TOWNSHIP 15 SOUTH, RANGE 11 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 63, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 142 AND DATED JANUARY 6, 1903, ORDERED BY G. H. FILNER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES AND SUBDIVISIONS OF SECTION 29 AND SECTION 32 IN TOWNSHIP 15, RANGE 11, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 10" X 8" X 6" FLINT STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 29-15-11 AT THE INTERSECTION OF TRANSIT LINES BETWEEN THE OPPOSITE 1/4 CORNERS, USING THE FRACTIONAL 1/4 CORNER ON THE INDIAN RESERVE LINE ON THIS **PERMANENT SURVEY**. SEE PACKET "M 137" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.00 CHAINS WEST TO THE 14" X 12" X 4" STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE SW1/4 OF SECTION 29-15-11

CENTER OF 29-15-11