

**NORTH 1/16 CORNER SOUTHWEST QUARTER SECTION 29, TOWNSHIP 15 SOUTH,
RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 63, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 142 AND DATED JANUARY 6, 1903, ORDERED BY G. H. FILNER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES AND SUBDIVISIONS OF SECTION 29 AND SECTION 32 IN TOWNSHIP 15, RANGE 11, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 14" X 12" X 4" STONE** FOR THE SOUTH 1/8TH CORNER OF THE NORTHWEST 1/4 OF SECTION 29-15-11 ON LINE BETWEEN THE FLAG THAT HE SET FOR THE WEST 1/4 CORNER OF SECTION 29-15-11 AND THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-15-11, AND ON LINE WITH THE OPPOSITE 1/8TH CORNER STONES TO THE NORTH AND SOUTH ON THIS **PERMANENT SURVEY**. SEE PACKET "M 137" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.00 CHAINS EAST TO THE 10" X 8" X 6" FLINT STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-15-11

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER 29-15-11