

**NORTH 1/16 CORNER NORTHWEST QUARTER SECTION 32, TOWNSHIP 15 SOUTH,
RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 63, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 142 AND DATED JANUARY 6, 1903, ORDERED BY G. H. FILNER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES AND SUBDIVISIONS OF SECTION 29 AND SECTION 32 IN TOWNSHIP 15, RANGE 11, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 16" X 10" X 6" STONE** FOR THE PERMANENT NORTHEAST CORNER THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 32-15-11 ON LINE AND HALFWAY BETWEEN THE STONE HE THAT FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-11 AND THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 32-15-11 ON THIS **PERMANENT SURVEY**. SEE PACKET "M 137" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS **PERMANENT SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.98 CHAINS WEST TO THE 22" X 12" X 3" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 32-15-11
- 2) 59.94 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-15-11
- 3) 19.98 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-11
- 4) 30.34 CHAINS EAST TO THE 24" X 10" X 4" STONE HE SET FOR THE PERMANENT FRACTIONAL CORNER BETWEEN SECTIONS 29 & 32-15-11 ON THE INDIAN LINE, AT THE NORTHWEST CORNER OF LOT 1 ON THE NORTH LINE OF THE NE1/4 OF SECTION 32-15-11
- 5) 19.98 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF THE NW1/4 OF SECTION 32-15-11
- 6) 80.10 CHAIN SOUTH TO THE 14" X 12" X 4" STONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 32-15-11 ON THE 3RD STANDARD PARALLEL

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 137, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 218 DATED OCTOBER 10, 1905 FOR G. H. GILDNER, PRINCIPAL PETITIONER, FOR A 40 FOOT WIDE ROAD IN TOWNSHIP 15, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/8TH CORNER OF THE NORTHWEST 1/4 OF SECTION 32-15-11 ON THIS ROAD SURVEY. ON PAGE 303 IN ROAD RECORD BOOK "D" IT STATES: THE ROAD WAS GRANTED BY THE COUNTY COMMISSION FROM THE NORTHWEST CORNER OF SECTION 32-15-11 TO THE ROAD ON THE INDIAN LINE, A DISTANCE OF 50.31 CHAINS. THE REMAINDER WAS **REJECTED** ON ACCOUNT OF EXCESSIVE DAMAGES ON NOVEMBER 11, 1905.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THE ALLOWED ROAD EXTENDS WEST ON THE SECTION LINES FOR 19.98-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-11 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY
- 2) THE ALLOWED ROAD EXTENDS EAST ON THE SECTION LINES FOR 19.97-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-11; THEN CONTINUES EAST ON THE SECTION LINES FOR 10.35 CHAINS TO THE STONE HE FOUND ON THE INDIAN LINE AND THE **END OF THE ROAD ALLOWED**; THE SURVEY NOTES SHOWS A DISTANCE EAST ON THE SECTION LINES OF 29.81 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-11; THEN EAST ON THE SECTION LINES FOR 80.31 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION

34-15-11; THEN EAST ON THE SECTION LINES FOR 80.24 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-15-11 AND THE END OF THE SURVEY NOTES

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 608 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 301 THROUGH 304 PETITIONED BY C. H. GILDNER AND OTHERS FOR A ROAD BEGINNING AT THE SOUTHWEST CORNER OF SECTION 25-15-10 THEN DUE EAST ON THE SECTION LINE AS NEAR AS PRACTICABLE FOR 6 MILES [PACKET 740 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 10, 1905, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/8TH CORNER OF THE NORTHWEST 1/4 OF SECTION 32-15-11 ON THIS ROAD SURVEY. THE ROAD WAS GRANTED AT 40 FEET WIDE BY THE BOARD OF COUNTY COMMISSIONERS FROM THE NORTHWEST CORNER OF SECTION 32-15-11 TO THE ROAD ON THE INDIAN LINE, A DISTANCE OF 50.31 CHAINS, THE REMAINDER IS **REJECTED** ON ACCOUNT OF EXCESSIVE DAMAGES, ON NOVEMBER 11, 1905.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THE ALLOWED ROAD EXTENDS WEST ON THE SECTION LINES FOR 19.98-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-11 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY
 - 2) THE ALLOWED ROAD EXTENDS EAST ON THE SECTION LINES FOR 19.97-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-11; THEN CONTINUES EAST ON THE SECTION LINES FOR 10.35 CHAINS TO THE STONE HE FOUND ON THE INDIAN LINE AND THE END OF THE ROAD ALLOWED; THE SURVEY NOTES SHOWS A DISTANCE EAST ON THE SECTION LINES OF 29.81 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-11; THEN EAST ON THE SECTION LINES FOR 80.31 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-15-11; THEN EAST ON THE SECTION LINES FOR 80.24 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-15-11 AND THE END OF THE SURVEY NOTES
- 4) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 36 AT THE REQUEST OF G. H. GILDNER TO MAKE A SURVEY OF THE BOUNDARY LINES OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 32-15-11 DATED MAY 28, 1909, SAID THAT **HE FOUND THE STONE AT THE INTERSECTION OF A HEDGE RUNNING EAST AND A WIRE FENCE RUNNING SOUTH** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 32-15-11 ON THIS **PERMANENT SURVEY**.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,318.7' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-11
 - 2) 1,318.7' EAST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE NW1/4 OF SECTION 32-15-11, AT 34 FEET WEST OF AN OSAGE HEDGE RUNNING SOUTH
 - 3) 2,003.4' EAST TO THE STONE HE FOUND IN PLACE ON THE INDIAN RESERVE LINE
 - 4) 1,320' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 32-15-11
 - 5) 2,640' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 32-15-11

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 32-15-11