

**WEST 1/4 CORNER SECTION 32, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 281 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 31 & 32-15-11.
  
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 63, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 142 AND DATED JANUARY 6, 1903, ORDERED BY G. H. FILNER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES AND SUBDIVISIONS OF SECTION 29 AND SECTION 32 IN TOWNSHIP 15, RANGE 11, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 32-15-11 ON THIS **PERMANENT SURVEY**. SEE PACKET "M 137" IN MISCELLANEOUS DRAWER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.90 CHAINS SOUTH TO THE ORIGINAL GOVERNMENT STONE HE FOUND AND **HE RESET** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 32-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL
  - 2) 19.98-1/2 CHAINS NORTH TO THE 16" X 10" X 3" STONE HE SET FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 32-15-11
  - 3) 39.97 CHAINS NORTH TO THE 22" X 12" X 3" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 32-15-11
  - 4) 79.93-1/2 CHAINS NORTH TO THE FLAG HE SET FOR THE WEST 1/4 CORNER OF SECTION 29-15-11
  - 5) 119.90 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-15-11

WEST QUARTER CORNER 32-15-11