

NORTHWEST CORNER SECTION 34, TOWNSHIP 15 SOUTH, RANGE 11 EAST

- 1) ON PAGE 277 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 36" X 14" X 3"** FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-15-11.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.91 CHAINS EAST TO THE 18" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-15-11
 - 2) 79.82 CHAINS EAST TO THE 18" X 16" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-15-11

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 228 AND APRIL 28, 1902 ORDERED BY C. D. HATCHER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE WEST 1/2 OF SECTION 35-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE GOVERNMENT STONE** AT THE NORTHWEST CORNER OF SECTION 34-15-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 54, AND ADDITIONAL INFORMATION IS IN PACKET "M 64" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 80.24 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 35-15-11
 - 2) 120.46 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35-15-11
 - 3) 160.46 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 35-15-11

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 137, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 218 DATED OCTOBER 10, 1905 FOR G. H. GILDNER, PRINCIPAL PETITIONER, FOR A 40 FOOT WIDE ROAD IN TOWNSHIP 15, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST OF SECTION 34-15-11 ON THIS ROAD SURVEY. ON PAGE 303 IN ROAD RECORD BOOK "D" IT STATES: THE ROAD WAS GRANTED BY THE COUNTY COMMISSION FROM THE NORTHWEST CORNER OF SECTION 32-15-11 TO THE ROAD ON THE INDIAN LINE, A DISTANCE OF 50.31 CHAINS. THE REMAINDER WAS **REJECTED** ON ACCOUNT OF EXCESSIVE DAMAGES ON NOVEMBER 11, 1905.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 80.31 CHAINS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-11; THEN WEST ON THE SECTION LINES FOR 29.81 CHAINS WEST TO THE STONE HE FOUND AT THE INDIAN RESERVE LINE TO END THE ROAD ALLOWED ON THIS ROAD SURVEY; THEN CONTINUES WEST ON THE SECTION LINES FOR 10.35 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-11; THEN CONTINUES WEST ON THE SECTION LINES FOR 19.97-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/8TH CORNER OF THE NORTHWEST 1/4 OF SECTION 32-15-11; THEN CONTINUES WEST ON THE SECTION LINES FOR 19.98-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-11 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY
 - 2) THE SURVEY NOTES SHOWS A DISTANCE EAST ON THE SECTION LINES FOR 80.24 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-15-11 AND THE END OF THE SURVEY NOTES

CONTINUED ON PAGE 2

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 608 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 301 THROUGH 304 PETITIONED BY C. H. GILDNER AND OTHERS FOR A ROAD BEGINNING AT THE SOUTHWEST CORNER OF SECTION 25-15-10 THEN DUE EAST ON THE SECTION LINE AS NEAR AS PRACTICABLE FOR 6 MILES [PACKET 740 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 10, 1905, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-15-11 ON THIS ROAD SURVEY. THE ROAD WAS GRANTED BY THE COUNTY COMMISSION FROM THE NORTHWEST CORNER OF SECTION 32-15-11 TO THE ROAD ON THE INDIAN LINE, A DISTANCE OF 50.31 CHAINS. THE REMAINDER WAS **REJECTED** ON ACCOUNT OF EXCESSIVE DAMAGES ON NOVEMBER 11, 1905. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 80.31 CHAINS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-15-11; THEN WEST ON THE SECTION LINES FOR 29.81 CHAINS WEST TO THE STONE HE FOUND AT THE INDIAN RESERVE LINE TO END THE ROAD ALLOWED ON THIS ROAD SURVEY; THEN CONTINUES WEST ON THE SECTION LINES FOR 10.35 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-15-11; THEN CONTINUES WEST ON THE SECTION LINES FOR 19.97-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/8TH CORNER OF THE NORTHWEST 1/4 OF SECTION 32-15-11; THEN CONTINUES WEST ON THE SECTION LINES FOR 19.98-1/2 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-15-11 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY
 - 2) THE SURVEY NOTES SHOWS A DISTANCE EAST ON THE SECTION LINES FOR 80.24 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-15-11 AND THE END OF THE SURVEY NOTES

NORTHWEST CORNER 34-15-11