

SOUTHWEST CORNER SECTION 34, TOWNSHIP 15 SOUTH, RANGE 11 EAST

- 1) ON PAGE 5 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 12" X 3"** ON A GENTLE SLOPE TO THE NORTH FOR THE CORNER TO SECTION 33 & 34-15-11 ON THE 3RD STANDARD PARALLEL ON OCTOBER 2, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 18" X 10" X 4" LIMESTONE THEY SET ON THE EDGE OF A DRAIN FOR THE SOUTH 1/4 CORNER OF SECTION 34-15-11
- 2) 80.00 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 21" X 8" X 4" LIMESTONE THEY SET ON A GENTLE EAST SLOPE FOR THE CORNER TO SECTIONS 34 & 35-15-11
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 201 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 390 TO 392 PETITIONED BY GEORGE W. DeCAMP AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD ON THE 3RD STANDARD PARALLEL BETWEEN TOWNSHIPS 15-11 AND 16-11 [PACKET 476 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 21, 1882, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON JANUARY 3, 1883 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOAR OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 22, 1883 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-15-11 ON THE 3RD STANDARD PARALLEL ON THIS RELOCATED ROAD. THE ROAD **VACATED** WAS ALL THAT PART OF THE SANTA FE ROAD BETWEEN THE CORNERS OF THE RELOCATED ROAD.

HIS NOTES SHOW THE FOLLOWING INFORMATION:

- 1) THIS RELOCATED ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL TO THE NORTHWEST CORNER OF SECTION 3-16-11; THEN EXTENDS SOUTH ON THE SECTION LINES FOR 18 CHAINS TO WHERE THE SANTA FE ROAD CROSSES SAID LINE TO COMMENCE THIS ROAD RELOCATION SURVEY
- 2) THIS RELOCATED ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL TO THE NORTHWEST CORNER OF SECTION 1-16-11; THEN CONTINUES EAST ON THE 3RD STANDARD PARALLEL FOR 27.92 CHAINS TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 36-15-11; THEN EXTENDS NORTH ON THE SECTION LINES FOR 5.86 CHAINS; THEN N. 73°30' E. FOR 16 CHAINS TO THE WEST EDGE OF THE BRIDGE OVER 142 CREEK AT THE TERMINUS OF THIS RELOCATED ROAD SURVEY
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 339 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 306 TO 308 PETITION BY MANLY B. SMITH AND OTHERS FOR THE VACATION OF PART OF THE SANTA FE TRAIL ROAD AND THE LOCATION OF A ROAD ON THE 3RD STANDARD PARALLEL BETWEEN TOWNSHIPS 15-11 AND 16-11 [PACKET 568 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 9, 1886, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON OCTOBER 14, 1886 BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MARCH 9, 1887 BY ROLAND LAKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-15-11 ON THE 3RD STANDARD PARALLEL TO BEGIN THIS ROAD SURVEY ON THE 3RD STANDARD PARALLEL. THE ROAD **VACATED** COMMENCED AT THE POINT WHERE THE SANTA FE TRAIL CROSSES THE WEST LINE OF SECTION 6-16-11, THENCE EAST FOLLOWING SAID TRAIL THROUGH THE NORTH 1/2 OF SECTIONS 6, 5 AND 4 TO THE POINT WHERE SAID TRAIL CROSSES THE EAST LINE OF SECTION 4-16-11 TO END THIS ROAD **VACATION**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS LOCATED ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 6-16-11 ON THE RANGE LINE TO BEGIN THIS ROAD LOCATION SURVEY
 - 2) THIS LOCATED ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 4-16-11 TO END THIS ROAD LOCATION SURVEY
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 228 AND APRIL 28, 1902 ORDERED BY C. D. HATCHER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE WEST 1/2 OF SECTION 35-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-15-11 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 54, AND ADDITIONAL INFORMATION IS IN PACKET "M 64" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.16 CHAINS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-15-11
- 2) 40.10 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE LOCATION FOR THE SOUTH 1/4 CORNER OF SECTION 34-15-11
- 3) 80.20 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 10" X 4" X 24" STONE MARKED "X" ON THE NORTH SIDE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 34-15-11
- 4) 120.30 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE 12" X 9" X 3" STONE MARKED "X" ON THE NORTH SIDE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 35-15-11
- 5) 160.40 CHAINS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-11

SOUTHWEST CORNER 34-15-11