

**NORTH 1/4 CORNER SECTION 35, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 275 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 14" X 3-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-15-11.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 39.92-1/2 CHAINS WEST TO THE 18" X 16" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-15-11
  - 2) 39.92-1/2 CHAINS EAST TO THE 36" X 8" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-15-11
  
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 228 AND APRIL 28, 1902 ORDERED BY C. D. HATCHER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE WEST 1/2 OF SECTION 35-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 35-15-11 ON THIS **PERMANENT SURVEY**. HE SAID THAT HE FOUND "BROWNS" WITNESS TREES. [MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914] HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 54, AND ADDITIONAL INFORMATION IS IN PACKET "M 64" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 35-15-11
  - 2) 40.22 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 35-15-11
  - 3) 120.46 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-15-11
  
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 2, 2009 FOR PROJECT NUMBER 09145-02 AND SURVEY F35001 IN THE SURVEY FILE FOR TOWNSHIP 15-11, A SURVEY OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 35-15-11 FOR JOHN SAMPLES, SAID THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTH 1/4 CORNER OF SECTION 35-15-11 FROM THE PRORATION OF ALVA J. SMITH'S SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 229 IN 1902 BUT THE POSITION WAS **NOT MONUMENTED** ON THIS SURVEY. HE SAID THAT SMITH'S FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 54.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,643.04' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 35-15-11
  - 2) 2,640.00' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 35-15-11
  - 3) 2,664.76' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 35-15-11
  - 4) 5,317.35' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL

NORTH QUARTER CORNER 35-15-11