

**SOUTH 1/4 CORNER SECTION 35, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 6 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 11" X 4"** ON A NORTHWEST SLOPE FOR THE SOUTH 1/4 CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON OCTOBER 2, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 21" X 8" X 4" LIMESTONE THEY SET ON A GENTLE EAST SLOPE FOR THE CORNER TO SECTIONS 34 & 35-15-11
- 2) 40.00 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 20" X 9" X 5" LIMESTONE THEY SET ON A SOUTHEAST SLOPE FOR THE CORNER TO SECTIONS 35 & 36-15-11

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 228 AND APRIL 28, 1902 ORDERED BY C. D. HATCHER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE WEST 1/2 OF SECTION 35-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 12" X 9" X 3" STONE MARKED PLUS ("+") ON THE NORTH SIDE** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL AT HALF WAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 35-15-11 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 54, AND ADDITIONAL INFORMATION IS IN PACKET "M 64" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.10 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-11
- 2) 40.10 CHAIN WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 10" X 4" X 24" STONE MARKED "X" ON THE NORTH SIDE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 35-15-11
- 3) 80.20 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE LOCATION FOR THE SOUTH 1/4 CORNER OF SECTION 34-15-11
- 4) 120.30 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-15-11
- 5) 160.46 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 33-15-11

- 3) THE KRETSINGER TIE BOOK FOR TOWNSHIP 15-11 SHOWS A **STONE** AT THE "S 1/4 CORNER SECTION 35-15-11" ON THE 3<sup>RD</sup> STANDARD PARALLEL DATED MAY 10, 1954.

- 1) 46.5' SE TO AN IRON PIN IN A STEEL FENCE POST
- 2) 48.5' SW TO AN IRON PIN IN A STEEL FENCE POST

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 2, 2009 FOR PROJECT NUMBER 09145-02 AND SURVEY F35001 IN THE SURVEY FILE FOR TOWNSHIP 15-11, A SURVEY OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 35-15-11 FOR JOHN SAMPLES, SAID THAT HE EXCAVATED FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL AT HALFWAY BETWEEN THE STONE THAT

HE FOUND AT THE SOUTHWEST CORNER OC SECTION 35-15-11 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-11.

- 1) 37.8' NNW TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH FACE OF A BRACE POST
- 2) 36.75' NORTH TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH FACE OF A CORNER FENCE POST
- 3) 44.35' NE TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH FACE OF A GATE POST
- 4) IN LINE WITH A FENCE TO THE NORTH
- 5) 2' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 370 EAST-WEST

HIS SURVEY SHOWED THE FOLLOWING INFORMATION:

- 1) 1,322.92' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE THEORETICAL POSITION FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 35-15-11
- 2) 2,645.84' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-15-11
- 3) 2,645.83' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 35-15-11
- 4) 2,652.59' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 35-15-11
- 5) 5,317.35' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 35-15-11

SOUTH QUARTER CORNER 35-15-11