

**SOUTHWEST CORNER SECTION 35, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 5 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 8" X 4"** ON A GENTLE EAST SLOPE FOR THE CORNER TO SECTIONS 34 & 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON OCTOBER 2, 1855.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 17" X 11" X 4" LIMESTONE THEY SET ON A NORTHWEST SLOPE FOR THE SOUTH 1/4 CORNER OF SECTION 35-15-11
  - 2) 80.00 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 20" X 9" X 5" LIMESTONE THEY SET ON A SOUTHEAST SLOPE FOR THE CORNER TO SECTIONS 35 & 36-15-11
  
- 2) G. M WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 20 & 21 FOR THE SURVEY OF THE "SANTA FE ROAD" IN THE NORTHEASTERN PART OF BRECKENRIDGE COUNTY THAT COMMENCED ON JANUARY 11, 1859 AND WAS ESTABLISHED FEBRUARY 29, 1859 IN COMMISSIONER JOURNAL ON PAGE 47 [SEE PACKET 158 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE], SAID THAT **THE SOUTH CORNER OF SECTIONS 34 & 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL IS 5 FEET SOUTH OF THE LINE** ON THIS ROAD SURVEY. SEE THE ROAD SURVEY FOR THE ANGLE STONES THAT HE SET ALONG THE ROUTE.
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 201 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 390 TO 392 PETITIONED BY GEORGE W. DeCAMP AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD ON THE 3<sup>RD</sup> STANDARD PARALLEL BETWEEN TOWNSHIPS 15-11 AND 16-11 [PACKET 476 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 21, 1882, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON JANUARY 3, 1883 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOAR OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 22, 1883 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS RELOCATED ROAD. THE ROAD **VACATED** WAS ALL THAT PART OF THE SANTA FE ROAD BETWEEN THE CORNERS OF THE RELOCATED ROAD.  
HIS NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) THIS RELOCATED ROAD EXTENDS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE NORTHWEST CORNER OF SECTION 3-16-11; THEN EXTENDS SOUTH ON THE SECTION LINES FOR 18 CHAINS TO WHERE THE SANTA FE ROAD CROSSES SAID LINE TO COMMENCE THIS ROAD RELOCATION SURVEY
  - 2) THIS RELOCATED ROAD EXTENDS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE NORTHWEST CORNER OF SECTION 1-16-11; THEN CONTINUES EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL FOR 27.92 CHAINS TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 36-15-11; THEN EXTENDS NORTH ON THE SECTION LINES FOR 5.86 CHAINS; THEN N. 73°30' E. FOR 16 CHAINS TO THE WEST EDGE OF THE BRIDGE OVER 142 CREEK AT THE TERMINUS OF THIS RELOCATED ROAD SURVEY
  
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 228 AND APRIL 28, 1902 ORDERED BY C. D. HATCHER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE WEST 1/2 OF SECTION 35-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 10" X 4" X**

**24" STONE MARKED WITH A PLUS ("+") ON THE NORTH SIDE FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS PERMANENT SURVEY. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 54, AND ADDITIONAL INFORMATION IS IN PACKET "M 64" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.**

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.10 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE LOCATION FOR THE SOUTH 1/4 CORNER OF SECTION 34-15-11
  - 2) 80.20 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-15-11
  - 3) 120.36 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 33-15-11
  - 4) 40.10 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 12" X 9" X 3" STONE MARKED "X" ON THE NORTH SIDE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 35-15-11
  - 5) 80.20 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-15-11
  - 6) 40.15 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 35-15-11
  - 7) 80.30 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 35-15-11
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 99, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 179 DATED OCTOBER 4, 1904, FOR A ROAD IN TOWNSHIP 15-11 FOR G. E. GORMAN, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 40.15 CHAINS TO THE GOVERNMENT 1/4 STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 35-15-11; THEN CONTINUES NORTH ON THE SECTION LINES FOR 40.15 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-15-11; THEN CONTINUES NORTH ON THE SECTION LINES FOR 80 CHAINS BY GOVERNMENT SURVEY TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-15-11 AT 30 FEET SOUTH OF A STONE WALL; THEN CONTINUES NORTH ON THE SECTION LINES FOR 80.63 CHAINS TO THE 22" X 9" X 3" STONE MARKED "R" ON THE SOUTH SIDE HE SET FOR THE NORTHWEST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
  - 2) 361.83 CHAINS NORTH TO THE STONE HE FOUND LOOSE ON THE GROUND AT THE EAST 1/4 CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
  - 3) 402.20 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "D" ON PAGES 229 THROUGH 232 FOR ROAD NUMBER 590 BY A PETITION BY G. E. GORMAN AND OTHERS FOR A ROAD IN TOWNSHIP 15-11 [PACKET 736 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON OCTOBER 5, 1904, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, 25 FEET EACH SIDE OF THE SECTION LINE, ON OCTOBER 6, 1904 AS NOTED BY JOHN LONGLEY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON OCTOBER 12, 1904 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE**

AT THE SOUTHWEST CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL TO BEGIN THIS ROAD SURVEY

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 40.15 CHAINS TO THE GOVERNMENT 1/4 STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 35-15-11; THEN CONTINUES NORTH ON THE SECTION LINES FOR 40.15 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-15-11; THEN CONTINUES NORTH ON THE SECTION LINES FOR 80 CHAINS BY GOVERNMENT SURVEY TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-15-11 AT 30 FEET SOUTH OF A STONE WALL; THEN CONTINUES NORTH ON THE SECTION LINES FOR 80.63 CHAINS TO THE 22" X 9" X 3" STONE MARKED "R" ON THE SOUTH SIDE HE SET FOR THE NORTHWEST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
  - 2) 361.83 CHAINS NORTH TO THE STONE HE FOUND LOOSE ON THE GROUND AT THE EAST 1/4 CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
  - 3) 402.20 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-15-11 IN WABAUNSEE COUNTY
- 
- 7) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 155 OF TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 78 & 79 DATED MARCH 4-6, 1909 AT THE ORDER OF LeMONT DeCAMP TO ESTABLISH THE CORNERS AND BOUNDARIES OF LOTS 3 & 4 OF SECTION 1-16-11 AND ANY OTHER CORNERS THAT MIGHT BE NECESSARY IN SAID SECTION TO ESTABLISH THE SAID CORNERS AND BOUNDARIES OF SAID LOTS, SAID THAT **HE FOUND THE STONE** AT THE CORNER TO SECTIONS 34 & 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE CORNER TO SECTIONS 35 & 36-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL TO SET A 14" X 10" X 6" STONE FOR THE PERMANENT NORTHWEST CORNER OF SECTION 1-16-11 [AKA NORTHWEST CORNER OF LOT 4].
  - 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 15-11 SHOWS A **STONE** AT THE "SE CORNER SECTION 34-15-11" ON THE 3<sup>RD</sup> STANDARD PARALLEL ON MAY 4, 1954.
    - 1) 41.4' SW TO A SPIKE IN A REA POLE
    - 2) 92.9' NW TO AN IRON PIN IN FRONT OF A MIDDLE STEEL FENCE POST
    - 3) 29.5' SOUTH TO A REA POLE LINE
  - 9) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 66 AT THE TOP OF THE PAGE SHOWS A **CORNERSTONE** AT THE "SE CORNER SECTION 34-15-11" ON THE 3<sup>RD</sup> STANDARD PARALLEL.
    - 1) 50.0' NW TO AN IRON PIN IN THE FENCE
    - 2) 21.5' NNE TO THE SOUTHEAST CORNER OF THE EAST HEADWALL OF A CULVERT
    - 3) 43.0' NE TO THE NEAR FACE OF AN 8" END HEDGE POST
  - 10) IN A FIELD BOOK LABELED "MJH MISC. 1965-1967" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE ON PAGE 46 FOR THE "LEAVELL PROPERTY DIVISION" IT SHOWS THAT **THEY FOUND** THE SOUTHWEST CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS SURVEY. THE SURVEY NOTES SAID THAT THE DISTANCE NORTH TO THE NORTHWEST CORNER OF SECTION 26-15-11 WAS 10,610.5 FEET FOR THE TWO MILES.
  - 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 2, 2009 FOR PROJECT NUMBER 09145-02 AND SURVEY F35001 IN THE SURVEY FILE FOR TOWNSHIP 15-11, A SURVEY OF THE

NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 35-15-11 FOR JOHN SAMPLES, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER AND **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP OVER THE TOP CENTER OF THE STONE.**

- 1) 40.7' SSE TO A CONCRETE NAIL & BOTTLECAP IN THE NORTH FACE OF A POWER POLE
- 2) 84.55' NE TO THE TOP CENTERLINE OF A 6" PIPE CORNER FENCE POST
- 3) 39.3' SOUTH TO A LINE OF FENCE RUNNING EAST-WEST
- 4) IN LINE WITH THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 370 TO THE EAST EXTENDED
- 5) 6.5' NORTH TO THE CENTERLINE OF THE TRAVELED WAY EAST-WEST ON THE CURVE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,649.90' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 35-15-11
- 2) 5,304.13' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 35-15-11
- 3) 2,645.83' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 35-15-11
- 4) 3,968.75' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE THEORETICAL POSITION FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 35-15-11
- 5) 5,291.67' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-15-11

SOUTHWEST CORNER 35-15-11