

**CENTER CORNER OF SECTION 36, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY OF SECTION 36-15-11 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE AND THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 36-15-11 THAT HE SURVEYED MARCH 16, 1882 AND HE FILED IN MISCELLANEOUS VOLUME 13 ON PAGE 395 ON MARCH 27, 1882 IN THE REGISTER OF DEEDS OFFICE, SAID THAT **HE SET A LIMESTONE 18" X 12" X 4"** FOR THE CENTER CORNER OF SECTION 36-15-11 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS SURVEY.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,319-1/4' WEST TO THE STONE HE SET FOR THE NORTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 36-15-11
- 2) 2,638-1/2' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 36-15-11
- 3) 1.322' NORTH TO THE STONE HE SET FOR THE EAST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 36-15-11
- 4) 2,644' NORTH TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 36-15-11
- 5) 2,634' EAST TO THE STONE HE SET FOR THE EAST 1/4 CORNER OF SEC. 36-15-11
- 6) 1,325-1/2' SOUTH TO THE STONE SET FOR THE WEST 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 36-15-11
- 7) 2,651' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 36-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL

CENTER OF 36-15-11