

**NORTHWEST CORNER SECTION 36, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 272 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 36" X 8" X 3-1/2"** FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-15-11.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.96-1/2 CHAINS EAST TO THE 26" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 36-15-11
- 2) 79.93 CHAINS EAST TO THE 16" X 3" X 4" LIMESTONE THEY SET FOR THE CORNER BETWEEN SECTIONS 25 & 36-15-11 ON THE EAST TOWNSHIP BOUNDARY

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 230 & 231 FOR A PETITION BY D. S. AVERY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-11, 16-11 AND 17-11 [PACKET 190 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 21 THROUGH 24, 1875, AND WAS ESTABLISHED ON JANUARY 3, 1876 AS A 50 FOOT WIDE ROAD, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 36-15-11 ON THIS ROAD SURVEY. HE NOTED THAT THE TOTAL LENGTH OF THIS ROAD IS "11 MILES, 41 CHAINS, 5 RODS AND 7-1/2 FEET".

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 36-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL AT A TURN TO THE SOUTHWESTERLY TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AND THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 15-17-11 TO THE TERMINUS OF THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 186 DATED SEPTEMBER 16, 1880, FOR A COUNTY ROAD IN TOWNSHIP 15-11, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 36-15-11 TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ONE MILE ON THE SECTION LINE TO THE STONE THE FOUND AT THE NORTHEAST CORNER OF SECTION 36-15-11 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 900 FEET TO A TURN TO THE NORTHWESTERLY TO 142 MILE CREEK

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 78 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 314 TO 316 PETITIONED BY DILL A. AVERY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 15-11 [PACKET 215 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS SURVEYED ON SEPTEMBER 16, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 5, 1880, AND WAS RECORDED ON NOVEMBER 12, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 36-15-11 ON THIS ROAD SURVEY. **[NOTE:** A PENCILED NOTE UNDER THE DRAWING STATES: "THIS ROAD WAS DECIDED ILLEGAL FEBRUARY 15, 1884 IN THE CASE STATE OF KANSAS VS. A. H. PUTMAN AS PETITION STATED TOWNSHIP 18, RANGE 11 INSTEAD OF 15-11. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 900 FEET TO A TURN TO THE NORTHWESTERLY TO 142 MILE CREEK
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 36-15-11 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY OF SECTION 36-15-11 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE AND THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 36 SURVEYED MARCH 16, 1882 AND FILED IN MISCELLANEOUS VOLUME 13 ON PAGE 395 ON MARCH 27, 1882 IN THE REGISTER OF DEEDS OFFICE, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 36-15-11 ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,635' EAST TO THE STONE WITH OLD MARKS ON IT HE RESET FOR THE NORTH 1/4 CORNER OF SECTION 35-15-11
  - 2) 5,270' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-15-11
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 228 AND APRIL 28, 1902 ORDERED BY C. D. HATCHER FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE WEST 1/2 OF SECTION 35-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 35-15-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 54, AND ADDITIONAL INFORMATION IS IN PACKET "M 64" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35-15-11
  - 2) 80.22 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 35-15-11
  - 3) 160.46 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-15-11
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 92, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 172 DATED APRIL 12, 1904 AT THE REQUEST OF E. W. CHANDON FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHWEST CORNER, THE SOUTH 1/4 CORNER, AND THE SOUTHEAST CORNER OF SECTION 24-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 26-15-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 34 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 155" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 80.54 CHAINS NORTH TO THE 27" X 12" X 3" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 23-15-11, AT 30 FEET SOUTH AND 30 FEET EAST OF THE CORNER OF A STONE WALL
- 2) 120.81 CHAINS NORTH TO THE 15" X 9" X 3" STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 23-15-11

HIS INFORMATION IS CONTINUED ON PAGE 3

- 3) 161.08 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE, AT 30 FEET EAST OF A BREAK IN THE STONE WALL
- 8) COMMISSIONER'S ROAD JOURNAL BOOK "C", PAGE 19  
 ON APRIL 28, 2004, A PETITION SIGNED BY THE LYON COUNTY COMMISSIONERS FOR THE VACATION OF A ROAD IN TOWNSHIP 15-11 WAS PRESENTED TO KAREN K. HARTENBOWER, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON APRIL 28, 2004 AND THE FINAL ORDER DATED APRIL 28, 2004 ORDERED THAT THE FOLLOWING ROAD BE VACATED:
- 1) THAT PORTION OF COUNTY ROAD "M" BETWEEN SECTIONS 25 AND 26 OF TOWNSHIP 15, RANGE 11 BETWEEN ROAD 382 AND ROAD 390 AND MORE PARTICULARLY DESCRIBED AS FOLLOWS: COMMENCING AT THE SOUTHEAST CORNER OF SAID SECTION 26, THENCE NORTH 60 RODS MORE OR LESS TO THE POINT OF BEGINNING OF THE ROAD TO BE VACATED, BEING ON THE NORTHERLY RIGHT-OF-WAY LINE OF ROAD 382 AS DESCRIBED IN ROAD RECORD PACKET 215 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE; THENCE CONTINUING NORTH BETWEEN SAID SECTIONS 25 AND 26 TO THE SOUTHERLY RIGHT-OF-WAY LINE OF ROAD 390, BEING 30 FEET SOUTH OF THE NORTHEAST CORNER OF SAID SECTION 26 AS DESCRIBED IN ROAD RECORD BOOK "B".
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 2, 2009 FOR PROJECT NUMBER 09145-02 AND SURVEY F35001 IN THE SURVEY FILE FOR TOWNSHIP 15-11, A SURVEY OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 35-15-11 FOR JOHN SAMPLES, SAID THAT HE CONSIDERED THAT THE NORTHEAST CORNER OF SECTION 35-15-11 WAS OBLITERATED. HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP FOR THE NORTHEAST CORNER OF SECTION 35-15-11 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER.
- 1) 49.5' SE TO A CONCRETE NAIL & BOTTLECAP IN THE NORTHWEST FACE OF A POWER POLE
- 2) 29.35' WSW TO A CONCRETE NAIL & BOTTLECAP IN THE EAST FACE OF A BRACE POST
- 3) 60.9' NNW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 4) 3.2' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M" NORTH-SOUTH
- 5) 5.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 380 TO THE EAST
- HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:
- 1) 2,640.00' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 35-15-11
- 2) 5,283.04' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 SECTION 35-15-11
- 3) 2,655.30' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 35-15-11
- 4) 3,982.95' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 35-15-11
- 5) 5,310.60' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL

NORTHWEST CORNER 36-15-11