

**SOUTH 1/4 CORNER SECTION 36, TOWNSHIP 15 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 6 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 7" X 4"** IN IMPROVEMENT FOR THE SOUTH 1/4 CORNER OF SECTION 36-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON OCTOBER 2, 1855, FROM WHICH:
  - 1) A BURR OAK 48" IN DIAMETER BEARS S. 55° W. AT 70 LINKS DISTANCE
  - 2) A BURR OAK 24" IN DIAMETER BEARS N. 78-1/2° W. AT 64 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

  - 1) 40.00 CHAINS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 20" X 9" X 5" LIMESTONE THEY SET ON A SOUTHEAST SLOPE FOR THE CORNER TO SECTIONS 35 & 36-15-11
  - 2) 40.00 CHAINS EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 42" X 12" X 7" LIMESTONE THEY SET ON AN EAST SLOPE FOR THE CORNER TO TOWNSHIP 15, RANGES 11 & 12
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY OF SECTION 36-15-11 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE AND THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 36 SURVEYED MARCH 16, 1882 AND FILED IN MISCELLANEOUS VOLUME 13 ON PAGE 395 ON MARCH 27, 1882 IN THE REGISTER OF DEEDS OFFICE, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 36-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 1,324' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 36-15-11
  - 2) 2,644' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-15-11
  - 3) 2,640' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-15-11
  - 4) 1,325-1/2' NORTH TO THE STONE HE SET FOR THE WEST 1/8<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 36-15-11
  - 5) 2,651' NORTH TO THE STONE HE SET FOR THE CENTER CORNER OF SEC. 36-15-11
  - 6) 3,973' NORTH TO THE STONE HE SET FOR THE EAST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 36-15-11
  - 7) 5,295' NORTH TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 36-15-11
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 201 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 390 TO 392 PETITIONED BY GEORGE W. DeCAMP AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD ON THE 3<sup>RD</sup> STANDARD PARALLEL BETWEEN TOWNSHIPS 15-11 AND 16-11 [PACKET 476 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 21, 1882, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON JANUARY 3, 1883 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOAR OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 22, 1883 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 36-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS RELOCATED ROAD. THE ROAD VACATED WAS ALL THAT PART OF THE SANTA FE ROAD BETWEEN THE CORNERS OF THE RELOCATED ROAD.

HIS NOTES SHOW THE FOLLOWING INFORMATION:

  - 1) THIS RELOCATED ROAD EXTENDS WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE NORTHWEST CORNER OF SECTION 3-16-11; THEN EXTENDS SOUTH ON THE SECTION LINES FOR 18 CHAINS TO WHERE THE SANTA FE ROAD CROSSES SAID LINE TO COMMENCE THIS ROAD RELOCATION SURVEY

- 2) THIS RELOCATED ROAD EXTENDS NORTH ON THE SECTION LINES FOR 5.86 CHAINS; THEN N. 73°30' E. FOR 16 CHAINS TO THE WEST EDGE OF THE BRIDGE OVER 142 CREEK AT THE TERMINUS OF THIS RELOCATED ROAD SURVEY
- 4) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK D, ON PAGE 78 AND DATED MARCH 1909, SAID THAT HE DID **NOT** FIND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 36-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F36003 IN THE SURVEY FILE FOR THIS TOWNSHIP DATED MARCH 10, 2003 FOR PROJECT NUMBER 03097-02, SAID THAT YINGLING DID **NOT** FIND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 36-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL IN THE 1909 PERMANENT SURVEY, AND ON THIS SURVEY HE DID **NOT** SEARCH FOR THE STONE.
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 30, 2013, FOR PROJECT NUMBER 13262-02 TO LOCATE A CERTAIN BRIDGE IN THE SOUTHWEST 1/4 OF SECTION 36-15-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT 13-37, SURVEY F36004 IN THE SURVEY FILE FOR TOWNSHIP 15-11, SAID THAT HE DEEMED THAT THE SOUTH 1/4 CORNER OF SECTION 36-15-11 WAS **LOST**. HE RESET THIS CORNER ON TRUE LINE AND HALFWAY BETWEEN THE SOUTHWEST CORNER OF SECTION 36-15-11 AND THE SOUTHEAST CORNER OF SECTION 36-15-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL. **HE SET A 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 36-15-11.
- 1) THIS CORNER FALLS IN OPEN PASTURE – NO TIES AVAILABLE
  - 2) 1,314.02' WEST TO THE 1/2" X 24" IRON PIN WITH "S. BROSEMER" CAP HE SET FOR A P. I. FOR COUNTY ROAD 360
  - 3) 2,041.82' EAST TO THE FOUND STONE AT THE NORTHWEST CORNER OF SECTION 6, TOWNSHIP 16 SOUTH, RANGE 12 EAST
  - 4) 2,642.02' EAST TO THE 5/8" X 24" IRON PIN HE SET FOR THE SOUTHEAST CORNER OF SECTION 36, TOWNSHIP 15 SOUTH, RANGE 11 EAST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING ADDITIONAL INFORMATION:**
- 1) 2,642.02' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE SQUARE 5/8" IRON PIN [AND STONE] HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-15-11 AT PROJECT STATION 0+00.00
  - 2) 3,168.79' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 3" X 8" LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF LOT 3 ON THE NORTH LINE OF THE NE1/4 OF SECTION 6-16-12 FROM THE EDMISTON SURVEY IN 1885

SOUTH QUARTER CORNER 36-15-11