

WEST 1/4 CORNER SECTION 36, TOWNSHIP 15 SOUTH, RANGE 11 EAST

- 1) ON PAGE 272 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 14" X 3.5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 35 & 36-15-11.

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY OF SECTION 36-15-11 TO ESTABLISH THE 1/4 CORNER ON THE EAST LINE AND THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 36-15-11 SURVEYED MARCH 16, 1882 AND FILED IN MISCELLANEOUS VOLUME 13 ON PAGE 395 ON MARCH 27, 1882 IN THE REGISTER OF DEEDS OFFICE, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 36-15-11 ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,319-1/4' EAST TO THE STONE HE SET FOR THE NORTH 1/8TH CORNER OF THE SE1/4 OF SECTION 36-15-11
 - 2) 3,638-1/2' EAST TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 36-15-11
 - 3) 5,272-1/2' EAST TO THE STONE HE SET FOR THE EAST 1/4 CORNER OF SECTION 36-15-11

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 2, 2009 FOR PROJECT NUMBER 09145-02 AND SURVEY F35001 IN THE SURVEY FILE FOR TOWNSHIP 15-11, A SURVEY OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 35-15-11 FOR JOHN SAMPLES, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 35-15-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 35-15-11 ON TRUE LINE AND HALFWAY BETWEEN THE NORTHEAST CORNER OF SECTION 35-15-11 AND THE SOUTHEAST CORNER OF SECTION 35-15-11 ON THE 3RD STANDARD PARALLEL.
 - 1) 25.00' WEST TO A 1/2" X 24" REBAR WITH HIS CAP
 - 2) 41.9' ESE TO A CONCRETE NAIL & BOTTLECAP IN THE WEST FACE OF A POWER POLE
 - 3) 43.3' EAST TO A LINE OF FENCE RUNNING NORTH-SOUTH
 - 4) 2.4' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M" NORTH-SOUTH
 - 5) 222.00' NORTH TO THE SOUTH EDGE OF A BRIDGE DECKHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,655.30' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 35-15-11
 - 2) 1,327.65' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 35-15-11
 - 3) 2,655.30' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-15-11 ON THE 3RD STANDARD PARALLEL
 - 4) 1,321.39' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/16TH CORNER OF THE SE1/4 OF SECTION 35-15-11
 - 5) 2,642.78' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 35-15-11
 - 6) 5,292.46' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 35-15-11

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 6, 2013 FOR PROJECT NUMBER 13233-02 AND SURVEY F35002 IN THE SURVEY FILE FOR TOWNSHIP 15-11, A SURVEY OF A

20.0 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 35-15-11 FOR ZACH HANSEN/EK REALTY, SAID THAT **HE FOUND THE 5/8" IRON PIN WITH HIS "LS 752" CAP** AT THE EAST 1/4 CORNER OF SECTION 35-15-11 FROM HIS EXISTING REFERENCE TIES FOR PROJECT NUMBER 09145-02 ON FILE AT THE COUNTY ENGINEERS OFFICE AND THE RETRACEMENT OF A PRIOR SURVEY RECORDED IN THE REGISTER OF DEEDS OFFICE AS DOCUMENT 2009-06758. THIS SECTION CORNER IS ALSO THE NORTHEAST CORNER OF THE 20.0 ACRE TRACT.

- 1) 25.00' WEST TO A 1/2" X 24" REBAR WITH HIS "LS 752" CAP
- 2) 41.9' EAST-SOUTHEAST TO A CONCRETE NAIL & BOTTLECAP IN THE WEST FACE OF A POWER POLE
- 3) 43.3' EAST TO A LINE OF FENCE RUNNING NORTH-SOUTH
- 4) 2.4' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M" NORTH-SOUTH
- 5) 222.00' NORTH TO THE SOUTH EDGE OF A BRIDGE DECK

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 908.00' WEST TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 20.0 ACRE TRACT
- 2) 1,321.39' WEST TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 35-15-11
- 3) 929.00' SOUTH TO THE SOUTHEAST CORNER OF THE 20.0 ACRE TRACT AS WITNESSED BY THE 1/2" IRON PIN WITH HIS "L.S. 752" CAP HE SET AT 40.00 FEET WESTERLY
- 4) 1,328.00' SOUTH TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 35-15-11

WEST QUARTER CORNER 36-15-11