

WEST 1/4 CORNER SECTION 19, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 27 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 4"** FOR THE WEST 1/4 CORNER OF SECTION 19-15-12 ON THE WEST TOWNSHIP BOUNDARY.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 21" X 15" X 2" LIMESTONE THEY SET FOR THE NORTHWEST CORNER OF SECTION 19-15-12 ON THE COUNTY LINE
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-15-12
-
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 92, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 172 DATED APRIL 12, 1904 AT THE REQUEST OF E. W. CHANDON FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHWEST CORNER, THE SOUTH 1/4 CORNER, AND THE SOUTHEAST CORNER OF SECTION 24-15-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT HE DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 24-15-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HE RAN THE RANGE LINE FROM THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 13-15-12 IN WABAUNSEE COUNTY TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-12, AND **HE SET A FLAG** FOR THE LOCATION FOR THE EAST 1/4 CORNER OF SECTION 24-15-12 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 34 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 155" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 80.49 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 13-15-11 IN WABAUNSEE COUNTY
- 2) 40.24 CHAINS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-15-11, WITH FENCE POSTS STANDING AT 56 LINKS SOUTHEAST, 47 LINKS NORTHEAST, 50 LINKS NORTHWEST, AND 47 LINKS SOUTHWEST
- 3) 19.97 CHAINS WEST TO THE 17" X 9" X 6" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 24-15-11
- 4) 39.94 CHAINS WEST TO THE 23" X 6" X 4" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 24-15-11
- 5) 59.91 CHAINS WEST TO THE 23" X 6" X 4" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 24-15-11
- 6) 79.88 CHAINS WEST TO THE 15" X 9" X 3" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 24-15-11

WEST QUARTER CORNER 19-15-12