

NORTHWEST CORNER SECTION 22, TOWNSHIP 15 SOUTH, RANGE 12 EAST

- 1) ON PAGE 441 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 5" X 5"** FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-15-12 ON THE COUNTY LINE.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.62-1/2 CHAINS EAST ON THE COUNTY LINE TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-15-12
 - 2) 79.25 CHAINS EAST ON THE COUNTY LINE TO THE 22" X 12" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-15-12

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 139, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 139 DATED SEPTEMBER 1 & 2, 1886 FOR S. HOLM, PRINCIPAL PETITIONER, FOR A ROAD ON THE WABAUNSEE COUNTY LINE, **APPARENTLY FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 22-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE COUNTY LINE FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-15-11 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE COUNTY LINE FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-15-13 TO BEGIN THIS ROAD SURVEY

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 340 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 310 TO 312 PETITIONED BY S. HOLM AND OTHERS FOR A ROAD ON THE LYON AND WABAUNSEE COUNTY LINE IN TOWNSHIPS 15-11, 15-12 AND 15-13 [PACKET 562 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 1, 1886, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 15, 1886 BY T. E. McMILLAN, CHAIRMAN OF THE LYON COUNTY BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MARCH 10, 1887 BY ROLAND LAKIN, LYON COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 22-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE COUNTY LINE FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-15-11 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE COUNTY LINE FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-15-13 TO BEGIN THIS ROAD SURVEY

- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A **PLAT OF PERMANENT SURVEY** OF SECTION 22-15-12, TO ESTABLISH THE LINES AND CORNERS OF THE NORTH 1/2 OF SECTION 22-15-12 MADE UNDER THE DIRECTION OF THE W. D. DEANS, COUNTY SURVEYOR OF WABAUNSEE COUNTY AND MATTHEW BROWN, COUNTY SURVEYOR OF LYON COUNTY ON JULY 18, 19 & 20, 1889 AT THE REQUEST OF S. HOLMES, AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PGE 528 AT THE REGISTER OF DEEDS OFFICE ON JULY 24, 1889, SAID THAT AFTER RUNNING THE SECTION LINES FROM THE STONES FOUND AT THE NORTHWEST CORNER OF SECTION 15 TO THE SOUTHWEST CORNER OF SECTION 22, AND FROM THE STONES AT THE NORTHWEST CORNER OF SECTION 21 TO THE NORTHEAST CORNER OF SECTION 23, THAT THE "PROCEEDED TO MAKE CALCULATIONS BY PROPORTIONAL MEASUREMENT AND FOUND THAT IT SEEMED

UNREASONABLE TO SET THE CORNER IN THAT WAY, AS OLD IMPROVEMENTS INDICATED THAT IT HAD BEEN ELSEWHERE". THEY USED THE TESTIMONY THAT THEY HAD RECEIVED AND **THEY SET A LIMESTONE 22" X 10" X 6"** FOR THE PERMANENT NORTHWEST CORNER OF SECTION 22-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE AT A POINT 9.5 FEET SOUTH AND 46 FEET EAST OF WHERE IT WOULD HAVE BEEN SET BY PROPORTIONAL MEASUREMENT ON THIS **PERMANENT SURVEY**.

- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 396 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 526 TO 528 PETITIONED BY W. W. WILSON AND OTHERS FOR TWO ROADS IN TOWNSHIP 15-12 [PACKETS 642 & 655 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 31, 1893, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON SEPTEMBER 11 & 12, 1893, WERE ESTABLISHED AS 40 FEET WIDE FOR THE EAST-WEST ROAD AND 50 FEET WIDE FOR THE NORTH-SOUTH ROAD ON OCTOBER 7, 1893, AS NOTED BY W. N. D. BIRD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 24, 1893 BY C. W. WILHITE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 22-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY. HE NOTED THAT THE SECTION CORNERS WERE IN AND DECLARED TO BE THE CENTER OF SAID ROAD.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECOND ROAD EXTENDS SOUTH ON THE SECTION LINES AT 25 FEET EACH SIDE OF THE SECTION LINE FOR 2 MILES TO THE SECTION CORNER HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-15-12 TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY

- 6) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 60 BY NOTICE FROM JOHN MARTIN TO MAKE A SURVEY OF THE LAND OWNED BY HIM IN SECTION 21-15-12 ON MARCH 17, 1910. ON APRIL 4, 1910 ON THE DAY TO COMMENCE THE SURVEY, AN AGREEMENT WAS MADE BETWEEN JOHN MARTIN, OTTO WHEAT, C. H. WATERS, L. E. BUSH, AND JOHN D. ECHOLS TO HAVE THE ONE FORTH AND ONE EIGHTH CORNER STONES ESTABLISHED ON THE WEST LINE OF THE SECTION AND ON THE CENTER LINE OF THE SECTION RUNNING NORTH. **HE SET A STAKE** FOR THE NORTHEAST CORNER OF SECTION 21-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE BY RUNNING A LINE FROM THE SOUTHEAST CORNER OF SECTION 21-15-12 OVER THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 21-15-12, AND AT THE SAME DISTANCE NORTH AS THE DISTANCE TO THE SOUTH, ON THIS **PERMANENT SURVEY**. HE NOTED THAT THIS POINT "COINCIDED TO THE BEST OF THE KNOWLEDGE AND MEMORY OF THE PARTIES PRESENT WITH THE LOCATION OF THE ORIGINAL STONE WHICH HAD BEEN WASHED OUT". THE SURVEY WAS MADE ON APRIL 4 & 5, 1910 AND WAS ENTERED ON MAY 5, 1910.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,653' SOUTH TO THE STONE HE FOUND IN PLACE AT THE EAST 1/4 CORNER OF SECTION 21-15-12
- 2) 5,306' SOUTH TO THE STAKE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 21-15-12

NORTHWEST CORNER 22-15-12